

## Features:

32-bit CPU  
8MB SDRAM,8MB Flash  
203 dpi resolution  
152mm(6'')/s high printing speed  
108mm printing width  
25.4-112mm (0.78'-4.56')adjustable media width  
Support TSPL EPL ZPL DPL command

## Specification:

General	
Model	OCBP-018
Material	White plastic housing
Interface	USB
Processor	32-bit CPU
Memory	8MB Flash Memory, 8MB SDRAM
Printer Head life	30KM
Power supply	Input□AC 100V-240V,50-60Hz,Output□DC 24V/2.5A
Sensors	Gap sensor,Blackmark sensor,Case-opening sensor
Gap height	2mm Min
Blackmark height	2mm Min
Font and barcode rotation	0°,90°,180°,270°
Compatible command	TSPL EPL ZPL DPL
Printing capability	
Printing method	Direct Thermal
Resoluiton	203 DPI
Print speed	152mm/s
Print width	108mm Max
Print length	1778mm Max
Barcode and character	
Barcode	1D barcode: Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13,EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST 2D barcode: PDF-417, Maxicode, DataMatrix, QR code
Media	
Media type	Continuous, gap,blackmark, folded and punched hole
Media width	26-116mm
Media thickness	0.06-0.20mm
Label roll capacity	No paper house
Label length	10-1778mm
Physical	
Dimension	185 mm(W)×85mm(H)× 85 mm(D)
Weight	Net:1.14kg Gross: 1.3kg
Package box	220*180*130mm
12 in 1 carton	560*460*285mm/17.1kg
Environment	

Working temperature& humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade , 10%~90% No condensation