

# Direct Thermal Bar Code Label Printer

## □(OCBP-020)

### Features:

1. Printing Width can be adjustable
2. Intelligent temperature controlling makes printer work more stably
3. Automatic calibration
4. Highly printing speed
5. Compatible with various shipping labels

### Specification

<b>Model</b>	OCBP-020
<b>Interface</b>	USB/USB+Bluetooth/USB+LAN
<b>Printer Head life</b>	50KM
<b>Power adaptor</b>	Input□AC 100-240V, 50□60Hz ; Output□DC 24V/1.5A
<b>Sensors</b>	Dual-media sensors: transmissive and reflective
<b>Printer driver</b>	Windows, MAC OS , Support IOS / Android
<b>Font and barcode rotation</b>	0°,90°,180°,270°
<b>Printer command</b>	TSPL command (CPCL/ESC/POS command-optional)
<b>Printing method</b>	Direct line thermal
<b>Resoluiton</b>	203 DPI
<b>Print speed</b>	120mm/s
<b>Print width</b>	20-76mm
<b>Available Max Paper Width</b>	80mm
<b>Barcode</b>	1D barcode: UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128 2D barcode: QR Code, PDF417
<b>Media</b>	
<b>Media type</b>	continuous paper, label paper, folded paper, tag paper
<b>Media width</b>	Max 80mm
<b>Media thickness</b>	0.06-0.30 mm
<b>Media core diameter</b>	25.4mm
<b>Paper roll diameter</b>	100mm (MAX)
<b>Physical</b>	
<b>Physical dimension</b>	200*160*139.5mm
<b>Weight</b>	Net:1.02kg , Gross1.40kg
<b>Package box</b>	235*220*170mm
<b>8 in one carton</b>	490*460*360mm/12kg
<b>Accessories</b>	USB cable,User Manual,Power adaptor
<b>Environment</b>	
<b>Working temperature&amp; humidity</b>	5 to 40 degrees centigrade, 25%~85% No condensation
<b>Storage temperature&amp; humidity</b>	-40 to 60 degrees centigrade , 10%~90% No condensation













