

## 2 Inch Direct Thermal Label Printer (M / N: OCBP - 201)

### Features:

- USB or USB+Bluetooth Interface for optional;
- Automatic paper checking function;
- Temperature adaptive control;
- Support receipt mode and label mode switching;
- Compatible with TSPL and ESC/POS command;
- Compact and sleek design for stylish counters.

### Specification:

Printing method	Direct thermal
Resolution	203DPI
Command	TSPL and ESC/POS
Mode switching	Support receipt mode and label mode switching (Command:HEX:1F 1B 1F 02 20 n 0D 0A,n=31/30.default n=30)
Print width	48mm
Printing speed	MAX:101mm/s MIN:50.8mm/s
Memory	DRAM: 256kb FLASH: 576kb
Printhead temperature	Thermistor
Paper exists detection	Micro switch
Interface	USB orUSB+Bluetooth
Paper presence detection	Paper presence detection
Barcode	CODE128 EAN128 ITF CODE39 CODE93 EAN13 EAN13+2 EAN13+5 EAN8 EAN8+2 EAN8+5 CODABAR POSTNET UPC-A UPC-A+2 UPC-A+5 UPC-E UPC-E+2 UPC-E+5 CPOST MSI MSIC PLESSEY ITF14 EAN14 Qrcode DM Code PDF417
Enlargement & rotation	0° 90° 270° 360° 1 to 10 times enlargement in both direction; 0° 90° 270° 360° rotation
Image	Monochromatic PCX, BMP image files can be load to FLASH
Paper type	Paper roll, sticker, adhesive sticker, etc
Paper width	20mm 60mm
Roll external	MAX 80mm
Roll inner diameter	MIN 25mm
Paper off type	Tear off
Power supply input	DC12V, 3A
Work environment	5 45°C, 20 80%RH(no condensation)
Storage	40 55°C 93%RH 40°C
environment	



OCBP-201





OCBP-201





OCBP-201





OCBP-201





OCBP-201





OCBP-201





OCBP-201







OCBP-201





## Relevant documents

[OCBP-201\\_spec](#)

