

(OCBP-M88) Thermal Receipt Printer 80MM Direct Wireless Pocket Hand Held Thermal Barcode Transfer Label Sticker Printer

(M/N:OCBP-M88)

Features:

- Front paper output structure makes paper feed smoother and less jams
- Fully body TPU wrap, strong anti-drop performance
- Support label interval sensor
- The width of the paper bin can be adjusted
- 50 diameter paper roller can be installed
- The USB Type-C interface can be both charge and communication
- The LCD screen can directly observe the printer status
- Support the physical button to set the printer
- Free label editing software, convenient for end users to use directly

Specification:

General	
Model	OCBP-M88
Color	Gray and white
Processor	32 bit CPU
Interface	USB type-C and Bluetooth
Printer head life	100Km
Battery	2600mAh, 7.4V 15Wh Non-removable battery
Charging time	4-5 hours
screen	1 inch TFT color screen
Sensors	Gap sensor,Cover opening sensor,Black mark sensor,Overheating sensor,paper end sensor
Working time	200meter printing, 7 days standby time
Power supply	5V DC/1A
Memory	8MB
software	Windows/Android/IOS/MAC
Safety standards	CE ,FCC,Rohs etc
Printing capability	
Printing method	Direct Thermal
Resoluiton	8 dots/mm(203 DPI)
Print speed	80mm/s
Print width/ length	72mm Max/ 1778mm Max
Print command	ESC/POS, CPCL command
Barcode and character	
Barcode	EAN-8, EAN-13, ITF, UPC-A, UPC-E, Codebar, Code93, Code39, Code128,QR Code,PDF417,Data Matrix,Grid Matrix
Character set	Alphanumeric/ GBK/Unicode
Media	
Media type	Continuous,Gap, Black mark
Media width	15-80mm
Media thickness	0.05-0.18mm
Media roll diameter	50mm Max
Physical	
Dimension	102mm*113mm*57mm
Weight/Package box	Net:390g Gross:531.3g/192.5×129.4×63.8mm
16 in 1 carton	384×345×295mm/10kg
Environment	
Working temperature&humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade , 10%~90% No condensation

Product overview:















