

3 Inch Bluetooth Thermal Label Printer

(M/N:OCBP-M89)

Features:



Support label interval sensor;

The width of the paper bin can be adjusted;

50mm diameter paper roller can be installed;

The USB Type-C interface can be both charge and communication;

The LED screen can directly observe the printer status;

Support the physical button to set the printer;

Free label editing software, convenient for end users to use directly.

Specification

General	
Model	OCBP-M89
Color	Black
Processor	32 bit CPU
Interface	USB type-C and Bluetooth

Printer head life	30km(printing density under 12.5%)/100 million pulses
Battery	2600mAh 7.4V removable battery
Charging time	4-5 hours
screen	0.91inch OLED
Sensors	Gap sensor,Cover opening sensor,Black mark sensor
Working time	2hours continuous, 7 days standby time
Power supply	5VDC/1A
Other features	Paper detection, manual shut down
Memory	96KDRAM and 700K Flash
software	Driver:Windows SDK:/Android/IOS
Printing capability	
Printing method	Direct Thermal
Resoluiton	8 dots/mm(203 DPI)
Print speed	50mm-80mm/s
Print width	72mm Max
Print length	300mmMAX
Print command	ESC/POS, TSPL CPCL command
Barcode and character	
Barcode	1D barcode: Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST 2D barcode: PDF-417, Maxicode, DataMatrix, QR code, Aztec
Character size	Font 0 to Font8
Character set	Alphanumeric/ Chinese
Media	
Media type	Continuous, Gap, Black mark
Media width	20-80mm
Media thickness	0.06-0.254mm
Media roll diameter	50mm Max
Physical	
Dimension	134.6*110.6*59.2mm(W*D*H)
Weight	Net:372g Gross:520g
Package box	164*138*85mm
20 in 1 carton	345*276*450mm(W*D*H) 11Kg
Environment	
Working temperature& humidity	0 to 40 degrees centigrade, 10%~80% No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade 10%~90% No condensation,











Relevant documents:

[OCBP-M89 Secondary development document](#)