

High Pixel 1D/2D Barcode Scanner

(Model No.: OCBS-2013)



Feautre:

1. High performance imaging technology;
2. 1MP High Pixel 1MP(1280*800);
3. Omni-directional scanning;
4. High compatibility for all major 1D and 2D symbols;
5. Can read the barcode on the screen and color barcode;
6. 4mil excellent scanning accuracy;
7. Multi special function setting supported;
8. Support ASCII extension code and special characters

Specification:

Performance Characteristics

Function	
Light source	White LED
Beep	Supported
Stand	Optional
Indicator	Green LED, beep

Scan performance		
Sensor		CMOS
Resolution		1280*800,256 gray levels
Maximum decoding speed		13mil UPC 40cm/s
Reading angle		horizontally 50 deg; vertically 20 Deg
Precision		≥4mil
Decode capability	1D	UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN (Bookland EAN), ISSN, Code 39, Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5 (Discrete 2 of 5), Matrix 2 of 5, Codabar (NW7), Code 128, UCC/EAN 128 (GS1-128), ISBT 128, Code93, Code 11 (USD-8), MSI/Plessey
	2D	PDF417, MicroPDF417, QR Code, DataMatrix, Han Xin Code, Aztec Code, GS1 Composite
Depth of field		Code 39(5mil)□50mm~120mm Code 39(10mil)□25mm~250mm UPC/EAN (13mil)□20mm~320mm Data Matrix(7.5mil)□63mm~150mm PDF417(6.6mil)□62mm~145mm
Sensitivity		Inclination ±45° @0°Roll and 0°Skew Rotation ±30° @0°Pitch and 0°Skew Deflection ±45° @0°Roll and 0°Skew
Electrical		
Interface		USB or USB virtual COM(virtual serial port)
Input Voltage		3.3v~5v DC
Standard Power		2.0w (400mA)
Max Power		2.5w (450mA)
DC adapter		Max 5.5V 1A
LED CLASS		Class I
User Environment		
Operate Temperature		-20 deg C ~ +60 deg C (-4 Deg F to 144 deg F)
Storage Temperature		-30 deg C ~ +70 Deg C (-22 Deg F to 158 deg F)
Humidity		5% - 95%(non- condensation)
Drop resistance:		1.5m (5.0ft) drops to concrete
IP class		IP54
Light intensity		Working: sun lights, fluorescent lights

Pictures Detail







