

High Performance 2D Barcode Scanner With Stand

(M/N:OCBS-2021)



Features:

Subvert traditional design, with simple assembly stand

0.3 million overall situation exposure, 60fps fast speed

3mil resolution bar code reading ability

Support reading many kinds of 1D&2D bar code

Support reading difficult bar codes (blurred, wrinkled, fuzzy, low contrast, high density)

Widely used in different host systems, such as windows 7/8/10, iOS, Android and Linux system, etc

Specification

| | |
|---------|-----------|
| General | |
| Model | OCBS-2021 |

| | |
|---------------------------------|--|
| Material | ABS+TPU |
| CPU | 32bit ARM |
| Prompt | Beep&LED |
| Scanning mode | Manual trigger/automatic induction |
| Interface | USB-HID,USB-VCP |
| Input Voltage | 3.6v~5.6v DC |
| current | Working current 142mAh,Standby current 42mAH |
| cable | 1.6M |
| Performance | |
| Sensor | CMOS |
| Light Source | White LED(lighting) red LED aiming |
| Scanning speed | 60fps |
| Resolution | ≥3mil |
| Decoding Depth | 60-360mm |
| Exposure | Global Exposure |
| COMS Image Size | 640x480 |
| Anti-ambient light interference | 0~5000Lux(fluorescent)~100,000Lux(Sunlight) |
| Barcodes | 1D:Codabar~Code11~Code39~Code32~Interleaved 2 of 5~Industrial 2 of 5~Matrix 2 of 5~Code93~Code128~GS1-128~UPC-A~UPC-E~EAN 8~EAN 13~GS1 DataBar~RSS14~GS1 DataBar Limited~GS1 DataBar Expanded~etc 2D: PDF417~Micro PDF417~QR Code~Micro QR~Data Matrix~Aztec Code |
| Scan Angle | Rotate 360°, inclination 65°, elevation 60° |
| Physical | |
| Weight | Gross:185g |
| Dimension | 163*68*80mm |
| Environment | |
| Working temperature& humidity | 0 to 45 degrees centigrade, 10%~80% No condensation |
| Storage temperature& humidity | -20 to 60 degrees centigrade , 10%~90% No condensation |



OCBS-2021







OCBS-2021





OCBS-2021





OCBS-2021





OCBS-2021

