

# OCBS-C006 Shenzhen handheld USB wired 1D CCD barcode scanner

## Model: OCBS-C006

### Feature

2500 pixel CCD sensor  
 280 scans per second  
 No need driver, plug and play.  
 Ability to scan 3mil density barcodes  
 Support reading bar codes from screen.  
 Support Manual/Auto/Continue scanning mode  
 Efficient decoding rate and ultra-low error rate.  
 Many kinds of one-dimensional bar code can be identified.

### Parameters:

<b>Performance Parameters</b>	Processor	32-bit ARM processor	
<b>Electrical Parameters</b>	Image Sensor	2500 pixel CCD sensor	
	Light Source	LED (wavelength 660nm ± 10nm)	
	Scan Speed	280 scans per second	
	Scan Angle	Skew ±55° roll ±25° pitch ±75°	
	Scanning Distance	(60% Contrast) (25mil) 40cm, (15mil) 32cm, (10mil) 22cm, (5mil) 11cm, (3mil) 3cm	
	Scanning Width	≤ 110mm	
	Resolution	≥0.1mm(4mil)	
	Minimum Contrast	15%	
	Decoding Capability	Code 39, Full ASCII Code 39, Code 32, Code 128, Code 93, Code 11, Codabar/NW7, All UPC/EAN/JAN code (EAN-13, EAN-8, UPC-A, UPC-E, EAN-128), Interleave 2 of 5, STD 2 of 5, Industrial 2 of 5, WPC code matrix 2 of 5, Chinese Postage Code, IATA, MSI/PLESSY, Italian Pharmacy Code, Industrial 2 of 5, BC-412 . UPC-A, UPC-E, Code 128, Code 93, Coda bar, IATA, MSI/PLESSY, Code 32, STD	
	<b>Electrical Parameters</b>	Voltage	4.5 ~ 5.5V DC V1 ± 5%
Current		Operating	100 ~ 110mA
		Standby	30 ~ 40mA
<b>Mechanical Parameters</b>	Dimensions	170mm(L)×60mm(W)×95mm(H)	
	Weight	185g	
	Case Material	ABS	
	Interfaces	USB	

<b>Environmental Parameters</b>	Operating Temperature	-20 °C ~ 50 °C
	Storage Temperature	-40 °C ~ 70 °C
	Humidity	0% ~ 98%(non-condensing)
	Illumination	0 ~ 70,000 lux
<b>Typical Scanning Distance</b>	5mil UPC	40mm - 160mm
	10mil Code93	20mm - 240mm
	15mil EAN13	40mm - 250mm
	20mil code128	40mm - 380mm
	40mil code128	80mm -520mm