

OCBS-D105 handheld barcode scanner bluetooth (model OCBS-D105)

| | |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Wireless Communications: | |
| Modulation | GFSK |
| Transmission rate | 200Kbps |
| Power | 10dBm |
| Transmission Distance | Visual straight line distance 300 meters |
| Antenna | Built-in spring antenna |
| Performance Characteristics | |
| Light Source | 650nm laser |
| Supported barcodes | EAN-8, EAN-13, UPC-A, UPC-E, Code 39, Code 93, Code 128, EAN128, Codaber, Industoal 2 of 5, Interleave 2 of 5, Matrix 2 of 5, MSI etc |
| Scanner Type: | Bi-directional |
| Scan rate | 48 ± 2 scan / second |
| Scan distance | 10-520mm |
| Scan width | 20mm @ window, 220mm @ 200mm |
| Resolution | 0.10mm (pcs0.9) |
| Depth of Field | 0 ~ 250mm (0.33mm, PCS 90%) |
| Working Way | Triggered or automatic (continuous mode) scanning |
| Physical Characteristics | |
| Memory: | 4M (Can store 100,000 barcodes) |
| Interfaces: | Standard configuration mini USB receiver; RS232 and PS2 optional |
| Current: | 96mA (working) 46mA (standby) |
| Battery: | Built-in rechargeable lithium ion battery (3.7V, 1900mAh) |
| Material | ABS + PC |
| Dimension: | 102mmX46mmX28mm |
| Weight: | 130g (with battery) |
| User Environment | |
| Operation Temperature | -20 Degree C ~ 45 Degree C |
| Storage Temperature | -20 Degree C ~ 60 Degree C |
| Humidity: | 5 ~ 95% relative humidity, non-condensing |
| Safe | |
| EMI / RFI: | CE & amp; FCC DOC compliance |
| Safety Standard | The second national laser safety standards |
| Ordering Information | |
| OCBS-D005 | Mini 433Mhz Wireless Barcode Scanner with screen and memory |
| OCBS-D105 | Mini blue tooth Wireless Barcode Scanner with screen and memory |

