

OCOM Handheld Wired 1D Laser Barcode Scanner

(M/N:OCBS-LA15)



Features:

- Handheld laser barcode scanner with auto sense function
- High scan rate (400 scans/sec) and long reading distance
- Excellent decoding capability
- USB and RS232 supported
- Grey -white and black color available

Specification

General	
Model	OCBS-LA15

Color	Gray-white and black
Material	ABS+PVC+PC
IP grade	IP52
Stand	Standard configuration
Interfaces	Default USB (RS232 customized)
Power consumption	105mW(Standby),320mW(Operating),550mW(Max)[Average]
Power supply	5V DC±5%
Button lifespan	Up to 100000 times
Electrostatic Discharge	15KV air discharge
Drop Specifications	Free fall 1.5m (concrete floor)
Language Supported	English, French (Canada), German (Germany), Italian (Italy), International Spanish,Turkish Q,Turkish F, Dutch (Netherlands),etc.
System supported	Linux,Android,Windows XP/7/8/10,MAC
Performance	
Light Source	Visual Laser 650nm
Decoding speed	400times/S
Reading distance	10mm-600mm
Reading mode	Laser
Triggle Mode	Manual,Auto-sensing
Error Rate	1/5000000
Prompt Method	Buzzer+Indicator light(LED)
Resolution	4mil
Print Contrast	30%
Scanning Angle	Rotation angle 30°, elevation angle 45°, declination angle 55°
Scanning Depth	Code 39 9.17mil(15 bit):5cm - 20cm Code93 10.83mil(16 bit):5cm - 23cm Code128 9.17mil(16 bit):5cm - 20cm EAN13 10.4mil:2cm - 25cm
Decoding Capability	Code25-Interleaved ,Code25-Standard,Code25-Matri,Code39, Code32,Code93,Code128,EAN/GS1/UCC128,Codabar,MSI, UK Plessey,EAN/JAN-13,UPC-A,EAN-8,Code11,UPCE, GS1 Omnidirectional,GS1 Limited,Febraban(Brazil Bank Code), China postal
Physical	
Weight	Gross:426
package	180*115*92mm
44 in 1 carton	600*450*385mm/20.9kg
Environment	
Working temperature& humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade , 10%~90% No condensation











