

Wireless 2D Barcode Scanner With Charge Base

(M/N:OCBS-W234)

Features:

1. Standard Long distance 2.4GHz Communication
2. Unblocked can transmit 80 meters
3. Million pixel high precision scanning engine
4. 190mA low power design can scan 40,000 times
5. Can work for more than 12 hours in a fully charged state
6. Standard charging and receive base
7. Big wireless buffer can transfer 1000 characters

| PHYSICAL CHARACTERISTICS | |
|----------------------------|---|
| Material | ABS+PC+TPU |
| Power supply | DC 5V ±5% |
| Operating current | 190mA [operating mode] |
| battery | 3.7V 2000mAH 18650 battery |
| Charging time | 6.5hours |
| Full working time | [12 hours |
| Weight | 170g±5g |
| PERFORMANCE CHARACTIESTICS | |
| Wireless Method | 2.4GHz |
| Transmission distance | 50-80M |
| Light Source | Red LED Aim +white light LED |
| Storage | 2M [about 40000 pieces barcodes] [can be customized] |
| Decode capability | Codabar,Code11,Code39/Code93,UPC/EAN,Code128/EAN128,InterLeaved2of5,Matrix2of5,MSI CODE,Standard2of5, QR CODE,DATA MATRIX, PDF417 |
| Resolution | Code39 5mil, QR 8.7mil, PCS45% |
| Depth of Field | 5MIL CODE39: 5--12 CM 15MIL CODE39 : 4--25 CM 10MIL CODE93 : 4--21 CM 15MIL UPC/EAN: 4--25 CM 20MIL QR : 4--25 CM |
| Scanning Speed | 400times/sec |
| Error rate | 1/500million |
| Setting Mode | Manual, Auto-sensing,Continuous Scanning |
| Scan Width | 5 * 5 cm ² -- 30 * 30 cm ² |
| Prompting Mode | Buzzer ,Indicator light [LED] |
| Print Contrast | Min 35% |
| Scanning Angles | Roll 0-360°, Pitch±65°, Yaw±60° |
| USER ENVIRONMENT | |
| IP level | ≥IP54 |
| Operating Temp | 0 to 50 °C / 32 to 122 °F |
| Storage Temp | 0 to 50 °C / 32 to 122 °F |
| Operating Humidity | 5 - 95% (non-condensing) |
| Storage Humidity | 5 - 95% (non-condensing) |
| Electrostatic Protection | 15KV |
| Shock Resistance | 1.5M free fall on concrete surface |



OCBS-W234





OCBS-W234





OCBS-W234





OCBS-W234





OCBS-W234





OCBS-W234

