

OCBS-W600 2.4G Wireless Small 1D Barcode Scanner with Memory

SPECIFICATION:

| PHYSICAL CHARACTERISTICS | |
|----------------------------------|---|
| Light Source: | Visible Laser Diode (VLD) @ 650 nm-670nm |
| Scanner Dimensions: | 164mm * 67mm * 95mm(W * H * D) |
| Receiver Dimensions: | 130mm*45mm*129mm(W * H * D) |
| Material: | ABS+TPR /Aluminium alloy |
| Weight: | 235g |
| Scanning Mode: | Hand-held; bidirectional Scanning Mode. |
| Indicator Light: | LED Red and Blue |
| Buzzer: | Buzzer Volume Adjustable |
| PERFORMANCE CHARACTERISTICS | |
| Width of Scan Field: | 60mm@30mm□From engine face□ 98mm@100mm□from engine face□ |
| Depth of Scan Field: | 2.5-600mm□Contrast 0.9 Density 0.25□ |
| Scan Speed: | 100 scans/sec |
| Scan Precision: | 0.10mm□4mil□ PCS0.9 |
| Bit Error Rate: | 1/(5million) |
| Decode Capability: | UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5 |
| Battery: | 3.7V/750mAh,Li-ion |
| Charge Time: | 3.0 Hours |
| Scan Time: | 30 Hours |
| Current: | 100mA (working); 40mA(standby) |
| Angles: | Pitch:60°; Tilt: 45° |
| Communication Distance: | 30m |
| Working Frequency: | 2.4G |
| Communication Interface: | USB |
| USER ENVIRONMENT CHARACTERISTICS | |
| Temperature: | 0degree C to 50degree C (Operating), -40degree Cto 70 degree C (Storage) |
| Relative Humidity: | 5%-90%(Non-Condensing) |
| Drop Specification: | Withstands repeated 1.5m drops to concrete surface |
| Ambient Illumination: | 0~100,000 LUX |
| Electrostatic Discharge: | Conforms to ±12KV air discharge and ±6KV of contact discharge |
| Safety Certificate: | CE, FCC, Class 2, RoHS |