

58mm embedded thermal printer

(M/N:OCKP-5803)

1. 90mm/s printing speed,
2. 50mm diameter paper house
3. Support multiple countries language code pages
4. Support graphical printing
5. Support multiple 1D and 2D bar-code printing
6. Printer head life 50km

| | |
|--------------------------|--------------------------------------|
| Model | OCKP-5803 |
| Printing method | Thermal line dot method |
| Paper type | Thermal paper roll |
| Interface | USB +RS232+TTL |
| Resolution | 203dpi(8dots/mm) |
| Paper width | 57.5±0.5mm |
| Printing speed | Max 90mm/s |
| Effective printing area | 48mm |
| Character set | ASCII, GB2312-80(Chinese), BIG5, etc |
| Character set | ANK(9*17,12*24)Chinese(24*24) |
| Paper roll diameter | Max:50mm |
| Paper thickness | 0.055-0.09mm |
| Print Life | 50Km |
| Bar-code types | Support 1D&2D bar-code printing |
| No Paper detection | Photoelectric detection |
| Paper near end detection | Photoelectric detection |
| Power adaptor | DC12V/2A |
| Dimensions | 114.8*132*86.4mm |
| weight | 150g |
| Package box | 140*130*80mm/250g |
| Operating temperature | 0°C~50°C |
| Operating humidity | 20%RH ~85% RH |
| Storage temperature | -20°C~60°C |
| Storage humidity | 5% ~90%RH |











Q.C.
PASSED

| Warranty | Serial # | Broken |
|----------|----------|--------|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

| END NC 0V | END RXD TXD DTR | END RXD TXD DTR | END D+ D- VCC |
|-----------|-----------------|-----------------|---------------|
| 3 2 1 | 4 3 2 1 | 4 3 2 1 | 1 2 3 4 |

POWER RS232 TTL USB

5VDC-12V
MICRO RS232+TTL+USB















无效
Seal is Broken
2024
4 | 5 | 6
10 | 11 | ✓

