

80mm Thermal Receipt Printer With Auto Cutter

(M/N:OCP-80K)

Specification

General	
Model	OCP-80K
Name	80mm desktop thermal printer with auto cutter
Color	Black
Interface	USB/USB+Lan/USB+BT/USB+WIFI/URL+WIFI/URL+BT/USB+RS232
Power Supply	Input:AC 100V-240V,50-60Hz,Output:DC 24V/2.5A
Cash drawer	DC 24V/1A
Printer head lifespan	150KM
Cutter	Auto cutter
Sensors	Paper out, cover open, cutter jam, paper jam and black mark detection(Optional)
Buffer	Input buffer:256K, NV Flash 256K
Accessories	Data cable, power adaptor, power cord, paper roller, CD, manual, Paper separator(optional)
OS supporting	Compatible with IOS/ Android/ Windows/Linux
Safety standards	CE, FCC, RoHS etc
Printing capability	
Printing method	Direct thermal line
Resolution	576 Dots/Line or 512 Dots/Line 8dots/mm, 203dpi
Printing speed	200mm/s (U/UR) 260mm/s (U/LU+BT/ U+WIFI) 300mm/s (U/LU/URL+BT/URL+WIFI)
Print width	72mm
Graphics printing	Supports bitmap download and print (each bitmap size Max.20K)
Printing Command	Compatible with ESC/POS
Barcode and character	
Barcode	1D barcode:UPC-A,UPC-E, AN13 EAN13 JAN8 EAN8 CODE39 ITF CODABAR CODE93 CODE128 2D barcode QR CODE Single USB or UR solution no QR code function
Character	Standard GB18030 simplified / traditional Chinese Fonts
Character size	384dots/line, ANK character, Font: A: 12*24dots, 1.5(W)*3.0(H) mm FontB:9*17dots, 1.1(W)*2.1(H)mm Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm
Japanese/Korea Optional	support
User-defined language	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/Iran/Latvian/Arabic/PT151.1251/PC737/WPC1257/Thai/Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151.1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
Media	
Paper type	Thermal roll paper
Paper width	48mm/52mm/56mm/64mm/68mm/76mm/80mm
Paper Thickness	0.06~0.08mm
Paper roll diameter	80mm Max
Paper separator	support
Physical	
Dimension	196*145*135mm
Weight	1.65kg
Package box	235*220*170mm
8 in 1 carton	475*445*358mm/14.4kg
Working temperature& humidity	
Working temperature& humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade, 10%~90% No condensation