

## OCOM 80MM USB Desktop Receipt Thermal Printer Auto Cut

(Model No.: OCPP-80X)

### Features:

- Supports multi 1D bar codes and 2D bar codes printing.
- 100M Ethernet port, ultra high speed data transmission.
- Supports 256KB NV Logo storage and 2M big buffer memory.
- Supports black mark detection and order reminding function,
- USB+RS232+LAN three types of communication Ports
- 250mm/s high speed printing



## Technical parameters

Printing method:	Direct thermal
Printing speed:	250mm/s
Roll width:	79.5±0.5mm
Print diameter:	Φ80mm
Paper thickness:	0.06-0.08mm
Column capacity:	576dots/line512 Dots/line
Line's pacing :	3.75mmAdjustable by commands
Print command:	Compatible with the ESC/POS command
Interface type:	Serial+USB+Lan
Cutters life:	1million cuts
Print head life:	100 km
Input buffer :	2048Kbytes
NV Flash:	256Kbytes
Power adaptor:	AC110V/240V50~60Hz
Power supply:	DC 24V/2.5A
Cash drawer supply:	DC 24V/1A
Work environment:	Temperature(045) humidity(1080%)Non- condense
Work environment:	Temperature(0-45) degree centigrade, humidity(10-80%) Non- condense
Storage environment:	Temperature(-1060°C); Humidity(1090%)
Character size:	ANKFontA:1.5*3.0mm/ FontB1.1*2.1mm
Barcode:	UPC-A/UPC-E/JA/EAN13/JAN8/EAN8/CODE39/ITF /CODE93/CODE128/QRCode/PDF417 (options)
Characters:	PC347Standard EuropeKatakanaPC850MultilingualPC860PortuguesePC863Canadian-FrenchPC865NordicWest EuropeGreekHebrewEast EuropeIranWPC1252PC866Cyrillic#2PC852 Latin2PC858IranIIatvianArabicPT1511251
Physical characteristics	Weight: 1.45Kg; Appearance size: 190×145×143mm (length * width * height)