

58mm Thermal Receipt Printer

(OCP-58E)

Product Introduction:

OCP-58E is a well-designed economic printer for common thermal bill printing, this model is with solid material, exquisite workmanship. Transparent cover design, simple and fashion, easy for users to know the paper rolls' Using status, OCP-58E adopt built-in power supply, not only can save space, but also easy for users to configure and use the printers. It's a very good choice for economical printing.

Product Features

- Simple and fashion, With solid material, exquisite workmanship.
- Easy paper install structure, simple and convenient to operate
- Built-in power supply design, to save space and more convenient to configure;
- Transparent cover design, the user can know the paper roll's using status anytime;
- Support GB18030 big font, easy to print uncommon characters
- Support multi language print, suitable for users all over the world;
- Support download and print LOGO & graphics ;
- Support Windows, Linux, Android and IOS system printing

Application Area

Shopping malls, restaurants, stores, warehousing, taxation, banking, medical, postal

Parameters

Items	Parameters
Print parameters	Printing Method Thermal Line
	Printing Width 48MM
	Resolution 360dots/Line [8dots/mm] [203dpi]
	Printing Speed 90mm/Second
Interface Type	USB [USB+Bluetooth]
	Line Spacing 3.75 mm [Can adjust line spacing by command]
Bar code Character	Line No. Font A: 32 character / Line Font B: 42 character / Line Simple, traditional Chinese-16 lines
	Character Standard GB18030 simplified / traditional Chinese Fonts
	Character Size ANK character [Font A] [1.5×3.0mm] [12×24dots] Font B [1.1×2.1mm] [9×17dots] [Simplified/Traditional Chinese] [3.0×3.0mm] [24×24 dots]
	Extended character set PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/Iran/Latvian/Arabic/PT151.1251/PC737/WPC1257/Thai/Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151.1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
Graphics printing	Bar code UPC-A/UPC-E/JAN13/EAN13/JAN8/EAN8/CODE39/ITF/CODABAR/CODE93/CODE128
	Supports bitmap download and print
Print commands	Type Thermal Roll
	Width 57.5±0.5mm
	Diameter ≤60mm
	Feed Method Easy feed (Clamshell feed)
Power	Commands ESC/POS
	Power Adaptor Input [AC 100V-240V, 50-60Hz] Output [DC 12V/2A]
Buffer	Cashier Drawer output DC 12V/1A
	Input Buffer 4K
physical characteristics	NV Flash 40K
	Weight 590g
Environment	Dimension 185*130*112(MM)
	Working Temp [5 ~ 45°C] Humidity [10 ~ 80%]
Reliability parameter	Storage Temp [10 ~ 50°C] Humidity [10 ~ 90%] [No dew]
	Print Head Life 50KM [print density ≤ 12.5]