

80mm thermal printer,80mm bill printer,80MM POS printer with auto cutter

Loading paper easy, waterproof, oil proof, dustproof;

260mm/sec high speed printing with automatic cutter, best printing quality and reliable performance;

Support print prompt and error alarm;

Support black mark sensor, reprint function;

Compatible with EPSON ESC/POS;

Support 128K bytes NV logo download store and print;

Support printer status monitor function, control printer's status at any time;

Support cash drawer driving;

80mm High Speed With Auto-cutter Pos Thermal Receipt Printer (Model: OCPP-804)

Specification:

| | |
|---------------------|---|
| Printing method | Direct thermal |
| Character size | ANK,FontA:12*24dots,FontB:9*17dots |
| Column capacity: | 576dots/line OR 512dots/line |
| Character set | PC347(Standard Europe), Katakana,PC850(Multilingual), PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), PC858, IranII, Latvian, Arabic, PT151(1251) |
| Barcode | JUPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODABAR/ITF/CODE39/CODE93/CODE128, QR code |
| Printing speed | 260mm/sec |
| Receive buffer | 64k bytes |
| NV Flash | 128k bytes |
| Paper width | 79.5±0.5mm |
| MCBF(life) | 100km |
| Printing command | Compatible with ESC/POS |
| Cash drawer control | DC 12-24V/1A |
| Paper thickness | 0.06-0.08mm |
| Cutter | Auto Cutter |
| Roll paper | 79.5±0.5mm* φ83mm |
| Interface | Serial/parallel/ USB |
| Driver | Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/win 7/Linux |
| Power supply | DC24V/2.5A |
| Power adapter input | AC 110V/220V, 50~60Hz; Output: DC 24V/2.5A |
| Dimension | 200x145x137mm |
| Net Weight | 1.56kg |

Product Details:



Relevant documents:

Do you want to know more product information?Please Click here.

Specification
User's Manual
Printer Driver

