

80MM Thermal Printer with Auto Cutter

(Model No.: OCPP-80H)

Features:

Desktop or wall-mounted type for option.

Supports multi 1D barcodes and 2D codes printing.

USB+RS232+LAN,3 interface

300mm /S high printing Speed

100M Ethernet port ultra high speed data transmission.

Supports 256KB NV Logo storage and 2M big buffer memory.

Supports black mark detection and order reminding function,

Compatible with OPOS driver.

Technical parameters

Printing method:	Direct thermal
Printing speed:	300mm/s
Roll width:	79.5±0.5mm
Print diameter:	Φ80mm
Paper thickness:	0.06-0.08mm
Column capacity:	576dots/line512 Dots/line
Line's pacing :	3.75mmAdjustable by commands
Print command:	Compatible with the ESC/POS command
Interface type:	Serial+USB+LAN
Cutters life:	1million cuts
Print head life:	100 km
Input buffer :	2048Kbytes
NV Flash:	256Kbytes
Power adaptor:	AC110V/240V50~60Hz
Power supply:	DC 24V/2.5A
Cash drawer supply:	DC 24V/1A
Work environment:	Temperature(045) humidity(1080%)Non- condense
Work environment:	Temperature(0-45) degree centigrade, humidity(10-80%) Non- condense
Storage environment:	Temperature(-1060°C); Humidity(1090%)
Character size:	ANKFontA:1.5*3.0mm/ FontB1.1*2.1mm
Barcode:	UPC-A/UPC-E/JA/EAN13/JAN8/EAN8/CODE39/ITF /CODE93/CODE128/QRCode/PDF417 (options)
Characters:	PC347Standard EuropeKatakanaPC850MultilingualPC860PortuguesePC863Canadian-FrenchPC865NordicWest EuropeGreekHebrewEast EuropeIranWPC1252PC866Cyrillic#2PC852 Latin2 PC858IranIIatvianArabicPT1511251



OCPP-80H





OCPP-80H





OCPP-80H





OCPP-80H



Attention: Press FEED or re-start to reset cutter when it or cover stuck, if not, open here and turn the gear to reset cutter

POWER BACK PAPER FEED





Power Plug for Option:



Relevant documents:

[OCP-80H SPEC](#)