

Features:

It can be used as top paper coming printer and front paper coming printer

It's built-in power adaptor, which avoid messy cord everywhere, saving much space

Support 8 kinds abundant interface combination

Supports multi 1D barcode and QR code printing

Support printer status monitoring function

Support printing queuing ticket function

100M Ethernet port, ultra high speed data transmission

256KB NV Logo storage and 256kb big buffer memory

48 or 80mm adjustable paper separator for option

150KM long life printer head

Specification:

General	
Model	OC-PP-50K
Name	80mm desktop thermal printer with auto cutter
Color	Black
Interface	USB(L/USB+Lan)/USB+BT/USB+WIFI/URL+WiFi/URL+BT/USB+RS232
Power supply	Input:AC 100V-240V 50-60Hz Output:DC 24V/2.5A
Cash drawer	DS-2411A
Graphics printing	Supports bitmap download and print (each bitmap size Max 20K)
Printer head lifespan	150KM
Cutter	Auto cutter
Sensors	Paper out, cover open, cutter jam, paper jam and black mark detection(Optional)
Buffer	Input buffer:256K/NV Flash 256K
Accessories	150k cable, power adaptor, power cord, paper roller, CD, manual, Paper separator(optional)
OS supporting	Compatible with /OS/ Android/ Windows
Safety standards	CE, FCC, RoHS etc
Printing Capability	
Printing method	Direct thermal line
Resolution	336 Dots/line or 512 Dots/Line(8dots/mm, 203dpi)
Printing speed	200mm/s (L/UR) 260mm/s (L/L+BT/L+WiFi) 300mm/s (URL/URL+BT/URL+WiFi)
Print width	72mm
Graphics printing	Supports bitmap download and print
Printing Command	Compatible with ESC/POS
Barcode & Character	
Barcode	1D barcode: UPC-A/UPC-E/JAN13/EAN13/JAN8/EAN8/CODE39/ITF/ CODABAR/CODE93/CODE128 2D barcode:QR CODE(Single USB or UR solution no QR code function)
Character	Standard GB18030 simplified / traditional Chinese Fonts
Character size	384dots/line, ANK character, Font: A: 12*24dots, 1.5*(W*3.0)H) mm FontB: 9*12dots, 1.1(W*2.4)H)mm Simplified/traditional: 24*24dots, 3.0(W)*3.0(H)mm optional
Japanese/Korea	Optional
User-defined language	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/Tranil/Latvian/Arabic/PT151_1251/PC737/WPC1257/Thai/Vietnam/PC864/PC1001/Latvian/PC10011/PF151_1251/(WPC1257)/(PC864)/(Vietnam)/(Thai)
Media	
Paper type	Thermal roll paper
Paper width	48mm/52mm/56mm/64mm/68mm/76mm/80mm
Paper thickness	12.5μ~18.0μm
Paper roll diameter	83mm Max
Paper separator	Optional
Package	
Dimension	196*145*135mm
Weight	1.85kg
Package box	300*190*180 mm
In 1 carton	615*370*335mm(21.5kg)
Environment	
Working temperature, humidity	0 to 45 degrees centigrade, 10%~80%, No condensation
Storage temperature, humidity	-20 to 60 degrees centigrade, 10%~90%, No condensation











