

# 80mm Thermal Printer with Auto Cutter

(Model No.: OCPP-80Z)

## Features:

Desktop or wall-mounted type for option;

Supports multi 1D/2D Barcode Printing;

USB+LAN interface for data transmission;

Support receipt comming reminder.

## Technical parameters

Printing method:	Direct thermal
Printing speed:	160 mm/s
Roll width:	79.5±0.5mm
Print diameter:	Φ80mm
Paper thickness:	0.06-0.08mm
Column capacity:	576dots/line512 Dots/line
Print command:	Compatible with the ESC/POS command
Interface type:	USB+LAN
Cutters life:	1million cuts
Print head life:	100 km
NV Flash:	256Kbytes
Power adaptor:	AC110V/240V,50~60Hz
Power supply:	DC 24V/1.5A
Cash drawer supply:	DC 24V/1A
Work environment:	Temperature(0-45) degree centigrade, humidity(10-80%) Non- condense
Storage environment:	Temperature(-10~60°C); Humidity(10~90%)
Character size:	ANK,FontA:1.5*3.0mm/ FontB:1.1*2.1mm
Barcode:	UPC-A/UPC-E/JA(EAN13)/JAN8(EAN8/CODE39/ITF /CODE93/CODE128, QR code, PDF417,Data Matrix )
Characters:	PC347(Standard Europe),Katakana,PC850(Multilingual),PC860(Portuguese),PC863(Canadian-French),PC865(Nordic),West Europe,Greek,Hebrew,East Europe,Iran,WPC1252,PC866(Cyrillic#2),PC852(Latin2), PC858,IranII,Latvian,Arabic,PT151(1251)
Physical characteristics	179*152*118mm



OCPP-80Z





OCPP-80Z





OCPP-80Z





OCPP-80Z



如果切刀被卡住, 请打开此盖, 调节切刀齿轮使切刀复位。  
Please open this cover to adjust the cutter gear if the cutter is locked and make the cutter reset.





OCPP-80Z



# Relevant documents:

OCPP-80Z Spec

OCPP-80Z CD