

## Features:

Mini size suitable for portable application

Windows, Java, Linux, Android (or Android +IOS ) operation system supported

Bluetooth, USB and RS232 communication supported

SDK for Android available

One printer can connect up to 8 smart devices (7 Android, one Apple device) via bluetooth

Low power consumption and large capacity Lithium battery (1500mAh), 4~5 days standby

Powered by rechargeable battery, power adapter, or car charger (specified models)

Higher print speed 90mm/sec

50km thermal printer head life

Multiple languages supported

ESC/POS command set compatible

## Specification:

| General               |                                                                                                   |
|-----------------------|---------------------------------------------------------------------------------------------------|
| Model                 | OCP-P-M06                                                                                         |
| Name                  | 58mm mini portable bluetooth thermal printer                                                      |
| Color                 | Black                                                                                             |
| Interface             | USB, RS-232, Bluetooth (optional)                                                                 |
| Battery               | 7.4V DC/ 1500mAh rechargeable li-ion battery                                                      |
| Power adaptor         | DC 9v/1.5-2A                                                                                      |
| Standby time          | 4-5days after fully charged                                                                       |
| Buffer                | Input buffer:Up to 20K,Flash:256K                                                                 |
| Other function        | Paper detection, Power detection, Manual shut down, 1D&QR Code Print                              |
| Device name           | Can be customized                                                                                 |
| TPH life              | 50KM                                                                                              |
| Password              | Enter default pairing code "1234", it can be customized or change by customers, At max 6 digitals |
| Accessories           | Data cable, power adaptor, power cord, paper roller, CD, manual                                   |
| Power plug dimension  | 3.5*1.1mm                                                                                         |
| OS supporting         | Windows & Android & IOS Systems                                                                   |
| Safety standards      | CE ,FCC,Rohs etc                                                                                  |
| Printing capability   |                                                                                                   |
| Printing method       | Direct thermal line                                                                               |
| Resolution            | 203DPI (8dot/mm)                                                                                  |
| Printing speed        | 70mm/sec (Max 90mm/sec)                                                                           |
| Print width           | 48mm                                                                                              |
| Continuous printing   | 120 pieces Thermal Roll for fully charged battery                                                 |
| Characters per Line   | Font A:32 character /Line<br>Simple,traditional Chinese:16 character /Line                        |
| Printing Command      | Compatible with ESC/POS                                                                           |
| Barcode and character |                                                                                                   |
| Character size        | FontA: 12*24dots, 1.5(W)*3.0(H)<br>Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm             |
| Character set         | Alphanumeric/ Chinese Kanji                                                                       |
| Media                 |                                                                                                   |
| Paper type            | Thermal roll paper                                                                                |
| Paper width           | 57.5±0.5mm                                                                                        |
| Paper feeding method  | Easy paper loading                                                                                |

|                               |                                                        |
|-------------------------------|--------------------------------------------------------|
| Paper roll diameter           | 40mm Max                                               |
| Paper thickness               | 0.06-0.08mm                                            |
| <b>Physical</b>               |                                                        |
| Dimension                     | 105*75*45mm                                            |
| Weight                        | Net:360g Gross:440g                                    |
| Package box                   | 190*120*70 mm                                          |
| 40 in 1 carton                | 380*475*340mm/18.36kg                                  |
| <b>Environment</b>            |                                                        |
| Working temperature& humidity | 0 to 45 degrees centigrade, 10%~80% No condensation    |
| Storage temperature& humidity | -20 to 60 degrees centigrade , 10%~90% No condensation |













