## OCOM Hot selling cheap android pos printer, pos printer android $\square \text{OCPP-M06} \square$

keywords: bluetooth printer, mini printer, portable printer

This mist injurted COP 4006 is a holded in PCS+ Admited ) Windows, Usine, Wilk compatible buttery genered Bloom pertialise models them up as post of the count by the CREAT CE and and Bustness Injuries count by specific communication ways together. This printer could be presented by multi-appealed buttery, power adaptive, or cer charges (depending on specified models). Special model can connect with 8 ments device for printing at same time. We have CE, FCC, and other requires

Overall Dimension (W×D×H)		105×75×45mm
Weight		134g
Color		Black
Print method		Thermal line printing
Print commands		ESC/POS compatible command set
Effective print width		48mm
Print speed		Jp to 90mm/sec
Resolution		8 dots/mm(203dpi)
Print font		12x24/24x24
Column capacity		32 columns/ 16columns
Character size		1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH)
Paper dimensions		58.0±0.1mm x diameter 40.0mm
Paper thickness		0.06 to 0.08mm
Character set		Alphanumeric/ Chinese Kanji
nterface		JSB, RS-232[Bluetooth (optional)
Flash		256KB
Power Adapter		W DC/2A
Battery Power		7.4V DC/ 1500mAh; battery can stay by for 4-5 days,
		when it is full power, it can print 120-150m paper
Other features		Paper detection, manual shut down
Working conditions		Temperature:-10~50 degC, Humidity:10%()90%
Storage conditions		Temperature:-20~70 degC, Humidity:5%(95%
Device name		Can be customized, letter and digital for option, at max 30 ASCII characters.
Password		Enter default pairing code "1234", it can be customized or change
		by customer itself. At max 6 digitals.
Power plug dimension		3.5*1.1mm
Ordering	OCPP-M06-88	Android, USB+COM+Bluetooth, Battery.
Info.	OCPP-M06-88-AI	Android+IOS, USB+COM+Bluetooth, Battery.
	OCPP-M06-8	Android, USB+COM+Bluetooth, without Battery;
	OCPP-M06-U	Mini printer, Android, USB+COM, without Battery.

Application Area

Compared to the traditional format in congrigation, the register of the properties to a congrigation of the register of the re