

**OCPP-M082 80mm 3 Inches RS-232 Port Thermal Printer
(Model: OCPP-M082)**

Specifications:

Dimensions (W × D × H)	98 × 103 × 45mm
Weight	280 g
Color	Black
Effective print width	72 mm
Printing method	Thermal Line Printing
Print command	ESC / POS compatible instruction set
Print speed	To 90mm/sec
Resolution	8 dots / mm (203DPI)
Print Font	In 12X24 / 24x24 in
Column capacity	48/ 24columns
Character size	1.5 × 3.0 mm (width x height) / 3.0x3.0mm (width x height)
Paper Size	Diameter of 80.0 mm to ± 0.1mm x30.0
Paper Thickness	0.06 to 0.08 mm
Character set	Alphanumeric / Chinese Text
Interface	USB, RS-232, Wifi, Bluetooth (optional)
Flash	256KB
Power Adapter	9V DC/2A
Battery Power	DC / 2000 mA 7.4V; battery can stay in 4-5 days, when it is full of strength, it can print 120-150M Paper
Other Features	Paper detection, power detection, manually shut down
Working conditions	Temperature: -10degreeC~50degreeC Humidity: 10%~90%
Storage conditions	Temperature: -20degreeC~70 degreeC Humidity: 5%~95%
Device Name	Can be customized to select letters and numbers up to 30 ASCII characters.
Password	Default Input pairing code "1234" It can be customized. Maximum 6 digitals.
Size of the power plug	3.5 * 1.1 mm

Product Details:

