

3 Inch Portable Mini Bluetooth Thermal Receipt Printer

(M/N:OCPP-M084)



Support Windows, Java, Android or IOS

Provide SDK for Android and IOS, driver for Windows PC

Bluetooth, USB and RS232 communication

2000mAh high capacity battery

Higher print speed 80mm/sec

50km TPH Life

A variety of 1D and 2D code supported

Built-in buzzer more easily for user get the printer status

Printing	
Printing method	Direct thermal
Print width	72mm
Column capacity	8dots/mm, 576dots/line
Printing speed	80mm/s
Interface	Bluetooth USB Serial
Printing paper	79.5±0.5mm×φ40mm
Line spacing	3.75mm (Adjustable by commands)
Column number	58mm paper: Font A - 32 columns/Font B - 42 columns/ Chinese,traditional Chinese - 16 columns
Character size	ANK Font A 1.5×3.0mm 12×24 dots Font B 1.1×2.1mm 9×17 dots Chinese,traditional Chinese:3.0×3.0mm 24×24 dots
Barcode Character	
Extension character sheet	PC347 Standard Europe Katakana PC850 Multilingual PC860 Portuguese PC863 Canadian-French PC865 Nordic West Europe Greek Hebrew East Europe Iran WPC1252 PC866 Cyrillic#2 PC852 Latin2 PC858 IranII Latvian Arabic PT151 1251
Barcode types	UPC-A/UPC-E/JAN13/EAN13/JAN8/EAN8/CODE39/ITF/CODABAR/CODE93/CODE128/QR/PDF417
Buffer	
Input buffer	32k bytes
NV Flash	64k bytes

Power	
Power supply	Input□AC 110V/240V, 50□60Hz
Power source	Output□DC 9V-2A
Physical characteristics	
Weight	0.19KG
Dimensions	111×88×41mm(D x W x H)
Environmental Requirements	
Work environment	Temperature (0□45) humidity(10□90%)
Storage environment	Temperature(-10□60°C) humidity(10□90%)
Reliability	
Printer head life	50KM

Relevant documents:

[OCPP-M084 Spec](#)

[CD files](#)