

OCP- M084 Factory supply 80mm handheld receipt printer bluetooth with android and IOS SDK

Specification

| Printing | |
|----------------------------|---|
| Printing method | Direct thermal |
| Print width | 72mm |
| Column capacity | 8dots/mm, 576dots/line |
| Printing speed | 80mm/s |
| Interface | Bluetooth□USB□Serial |
| Printing paper | 79.5±0.5mm×φ40mm |
| Line spacing | 3.75mm (Adjustable by commands) |
| Column number | 58mm paper: Font A - 32 columns/Font B - 42 columns/ Chinese,traditional Chinese - 16 columns |
| Character size | ANK□Font A□1.5×3.0mm□12×24 dots□ Font B□1.1×2.1mm□9×17 dots□ Chinese,traditional Chinese:3.0×3.0mm□24×24 dots□ |
| Barcode Character | |
| Extension character sheet | PC347□Standard Europe□Katakana□PC850□Multilingual□PC860□Portuguese□PC863□Canadian-French□PC865□Nordic□West Europe□Greek□Hebrew□East Europe□Iran□WPC1252□PC866□Cyrillic#2□PC852□Latin2□PC858□IranII□Latvian□Arabic□PT151□1251□ |
| Barcode types | UPC-A/UPC-E/JAN13□EAN13□JAN8□EAN8□/CODE39/ITF/CODABAR/CODE93/CODE128/QR/PDF417 |
| Buffer | |
| Input buffer | 32k bytes |
| NV Flash | 64k bytes |
| Power | |
| Power supply | Input□AC 110V/240V, 50□60Hz |
| Power source | Output□DC 9V-2A |
| Physical characteristics | |
| Weight | 0.19KG |
| Dimensions | 111×88×41mm(D x W x H) |
| Environmental Requirements | |
| Work environment | Temperature (0□45) humidity(10□90%) |
| Storage environment | Temperature(-10□60°C) humidity(10□90%) |
| Reliability | |
| Printer head life | 50KM |