


One-to-One Paired up 2d Wireless Radio Wave Barcode Scanner with Memory

PHYSICAL CHARACTERISTICS	
Light Source	Visible Laser Diode (VLD) @ 650 nm
scanner Dimensions(W * H * D)	168*72*93 mm
receiver Dimensions(W * H * D)	130*75*129mm
Material	ABS+TPU /Aluminium alloy
scanner Weight	190g (Including battery)
receiver Weight	180g
User Mode	Hand-held
Scanning Mode	Manual/ Automatic
Indicator Light	Scanner LED Red and Blue receiver Left Green+ right Blue
Buzzer	Buzzer Volume Adjustable

PERFORMANCE CHARACTERISTICS	
Width of Scan Field	60mm@30mm (From engine face) 98mm@100mm (from engine face)
Depth of Scan Field	10-450mm (Contrast 0.9 Density0.25)
Scan Speed	300 scans/sec
Scan Precision	0.10-0.825mm
Bit Error Rate	1/(5million)
Symbolologies Supported	1D <u>UPC-A</u> , <u>UPC-E</u> , <u>EAN-8</u> , <u>EAN-13</u> Code 39, Code 32, Coda bar ,Code 128, ISBT 128, Code 93, Interleaved 2 of 5 Discrete 2 of 5 ,CODE11, MSI,  名称 <u>GS1-DataBar</u> , <u>UCC/EAN-128</u> , <u>BooklandEAN</u> , <u>Bookland EAN/ISBN</u> , <u>Trioptic Code39</u> , <u>CouponCodeGS1</u> , <u>DataBar-14</u> , <u>SETUP128</u> <u>GS1Data Bar Limited</u> , <u>GS1Data Bar Expanded</u> , <u>RSS</u>
	2D <u>PDF417</u> <u>DataMatrix(DM)</u> <u>QR</u>
Battery	3.7V/1200mAh, Li-ion
Charge Time	2.5 Hours

Scan Time	10 Hours
Scan Current	95mA
Standby current	25mA
Maximum Pitch Angles	60°
Maximum Tilt Angles	45°
Working Frequency	433MHz
Communication Distance	200m (Open Places)
Flash	16MB
Communication Interface	USB