


## One-to-One Paired up 2d Wireless Radio Wave Barcode Scanner with Memory

PHYSICAL CHARACTERISTICS	
Light Source	Visible Laser Diode (VLD) @ 650 nm
scanner Dimensions(W * H * D)	168*72*93 mm
receiver Dimensions(W * H * D)	130*75*129mm
Material	ABS+TPU /Aluminium alloy
scanner Weight	190g (Including battery)
receiver Weight	180g
User Mode	Hand-held
Scanning Mode	Manual/ Automatic
Indicator Light	Scanner LED Red and Blue receiver Left Green+ right Blue
Buzzer	Buzzer Volume Adjustable

PERFORMANCE CHARACTERISTICS	
Width of Scan Field	60mm@30mm ( From engine face ) 98mm@100mm ( from engine face )
Depth of Scan Field	10-450mm (Contrast 0.9 Density0.25)
Scan Speed	300 scans/sec
Scan Precision	0.10-0.825mm
Bit Error Rate	1/(5million)
Symbologies Supported	1D UPC-A, UPC-E, EAN-8, EAN-13 Code 39, Code 32, Coda bar ,Code 128, ISBT 128, Code 93, Interleaved 2 of 5 Discrete 2 of 5 ,CODE11, MSI,  名称sey GS1-DataBar, UCC/EAN-128,BooklandEAN, Bookland EAN/ISBN , Trioptic Code39, CouponCodeGS1, DataBar-14, SETUP128 GS1Data Bar Limited, GS1Data Bar Expanded, RSS
	2D PDF417 DataMatrix(DM) QR
Battery	3.7V/1200mAh, Li-ion
Charge Time	2.5 Hours
Scan Time	10 Hours
Scan Current	95mA
Standby current	25mA
Maximum Pitch Angles	60°
Maximum Tilt Angles	45°
Working Frequency	433MHz
Communication Distance	200m (Open Places)
Flash	16MB
Communication Interface	USB