

2016 Date low cost pos terminal pocket
(M / N: P8000)

Android 4.4 operating system.
Adopts Qualcomm 1.2GHz quad-core processor.
4.0 inch IPS capacitive touch screen.
Safe and reliable design
Passed Unionpay PBOC L1 & amp; amp; L2; Seizure of security certification of the past PIN.
direct connect access Unionpay POS network.
Support receipt printing and bar code reading
Support for magnetic stripe card, smart card, contactless card.

system settings	
CPU	Qualcomm quad-core 1.2GHz
OS	Android 4.4
RAM / ROM	512MB eMMC ROM; 512MB DDR2 RAM; SD card support external microphone, 32 GB maximum
Display	4.0 inch capacitive multi-touch; 480 * 800 IPS screen
Keyboard	3 Press System keys, 15 physical keys (including the power key, customized key, POS Cipher key and Command key)
Battery	Lithium polymer battery, 5700mAh
functional configuration	
Camera	5M AF rear camera (flashlight support), wide-angle front camera 0.3M
Printer	Integrated 2-inch thermal printer
Navigation	Integrated GPS, AGPS Support
Lighting	System indicator light, POS indicator light
Audio	Built-in speaker, buzzer, microphone, vibrator
Sensors	Sensor gravity
POS	
Payment Sound Wave	Support
Magnetic strip card	MSR Triple track, bi-directional scanning ISO7811, 7812
IC Card	1 Slot, Support 1.8V / 3V / 5V, ISO7816, and PBOC EMV
Contactless card	13.56, ISO / IEC 14443 Type A / B, qPBOC
SAM Card	1 SAM Slot, 7816
key cipher	Integrated keyboard
network settings	
Type of network	WCDMA / GSM
Spectrum Network	WCDMA 2100MHz GSM / GPRS / EDGE 850/900/1800 / 1900MHz
WLAN	802.11 a / b / g / n Integrated antenna
Voice / Data Service	Support
WPAN	Bluetooth V4.0 + EDR
external interface	
USB interface	Micro USB2.0, USB OTG Support
Jack Charger	DC JACK
Jack supply	Pogo Pin, 5V - 500mA
Communication	RS232
physical parameters	
Dimensions	H 205mm * 82mm / 67mm * 33mm W D
Weight	500g (battery included)
Operating temperature	-20 ° C - 60 ° C
Storage temperature	-40 ° C - 80 ° C
Humidity	10% - 90% RH non-condensing
Drop test	1.0 m fall protection
Roll Drop Test	500 times
ESD protection	± contact discharge 8KV; ± 15KV air discharge
Development environment	
system environment	Android 4.4 / SP-UI
Development environment	SDK
Management software	Following PC management / MDM