

# 15.6 Inch Windows/Android Touch POS Terminal

(M/N:POS-1516)

## Features:

1. 15.6 inch BOE brand new LCD screen
2. Multi-point projected capacitive touch panel
3. Removable bottom plate for smaller packaging and less shipping cost
4. The main screen supports large angle rotation to meet any observation angle
5. Borderless screen , the front protects against direct water splashes
6. Ultra-thin body makes the product more concise and stylish
7. Thick and stable aluminum base
8. Cable slots inside the base make the cable more tidy
9. Customer display, secondary screen and MSR installation position is reserved on the shell

## Specification

| Model               | POS-1516-W   | POS-1516-A   |
|---------------------|--|--|
| Name                | 15.6 inch Windows touch screen pos terminal  | 15.6 inch Android touch screen pos terminal          |
| Housing             | ABS plastic machine body with aluminium alloy base   |  |
| Color               | whole black color machine body   |  |
|                     |  |  |
| Main screen         | 15.6 inch touch screen monitor   |  |
| Resolution          | 1366*768, 1920*1080 for option   |  |
| Brightness          | 300cd/m <sup>2</sup>   |  |
| View angle          | Horizon: 160; Vertical :150  |  |
| Touch screen        | Multi-point projected G+G capacitive touch   |  |
| Sub-display         | 15.6inch display W or W/o touch function, resolution 1366*768 or 1920*1080 resolution for option |  |
| Customer display    | 2*20 VFD or 2*20 LCD mounted to back cover for option  |  |
| <b>Performance</b>  |  |  |
| Motherboard         | Intel Celeron Bay Trail J1900 2.0GHz usually or intel core I3 / I5 4 generation CPU for option   | RK3566, quad core 1.8GHz CPU                         |
| System Memory       | 1*SO-DIMM DDRIII slot, support1333*/1600 4GB (default) 2GB/8GB for option                        | On board 2GB DDRIII,4GB for option                   |
| Storage device      | Msata SSD 64GB or higer, up to 256GB   | 32GB eMMC,   |
| Audio               | On board Real Tek ALC662 audio chip ALC5640  | On board Real Tek audio chip ALC5640                 |
| LAN                 | 10/100Mbs, Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module       | 10M/100M RTL8201F,10M/100M/1000M RTL8211E for option |
| Operating System    | Windows 7/8/10, Embedded,WEPOS,Linux   | Android 11   |
| <b>Connectivity</b> |  |  |

|                                     |  |                         |
|-------------------------------------|--|-------------------------|
| External I/O port(J1900 and RK3288) | power button*1   |                         |
|                                     | 12V DC in jack*1   |                         |
|                                     | LAN:RJ-45*1  |                         |
|                                     | USB *4   |                         |
|                                     | COM(RS232) * 1   | COM(RS232) * 2          |
|                                     | VGA(15Pin D-sub)*1   | RJ11 for Cash drawer *1 |
| Audio out*1                         | MIC in*1 ,Audio out*1  |                         |
| <b>Package</b>                      |  |                         |
| Weight                              | Net 4.0 Kg Gross 5.0 Kg  |                         |
| Package with foam inside            | 460*185*420 mm for single screen   |                         |
| <b>Environment</b>                  |  |                         |
| Operating temperature               | 0 to 40 degrees centigrade   |                         |
| Storage temperature                 | -10 to 60 degrees centigrade   |                         |
| Working humidity                    | 10%~80% No condensation  |                         |
| Storage humidity                    | 10%~90% No condensation  |                         |
| <b>Accessories</b>                  |  |                         |
| Power adapter                       | 110-240V/50-60HZ AC power input ,DC12V/5A output adaptor                   |                         |
| Power cable                         | Power cable plug compatible with USA /EU / UK etc and customized available |                         |
| CD driver                           | Motherboard driver and touch driver inside                                 |                         |
| <b>Other</b>                        |  |                         |
| Compliance                          | FCC Class A/CE Mark/LVD/CCC  |                         |



















| 点选鲜果茶       |          | 精选奶茶     |     | 风味小吃   |     | 饮品速递  |     |
|-------------|----------|----------|-----|--------|-----|-------|-----|
| 01. 鹿茸西柚鲜果茶 | 1<br>¥18 | 台式奶茶     | ¥13 | 奶盖茶    | ¥15 | 布丁奶茶  | ¥16 |
| 02. 满杯奇果茶   | 1<br>¥18 | 樱花阿蒙山的奶茶 | ¥18 | 桃酥奶茶   | ¥20 | 珍珠奶茶  | ¥17 |
| 03. 奶盖茶     | 1<br>¥15 | 珍珠奶茶     | ¥15 | 珍珠奶茶   | ¥17 | 相思豆奶茶 | ¥15 |
| 04. 桃酥奶茶    | 1<br>¥20 | 蜜桃大吉奶茶   | ¥18 | 香米抹茶红豆 | ¥17 |       |     |
| 05. 珍珠奶茶    | 1<br>¥17 |          |     |        |     |       |     |

清空(0) 结算

点击选择会员

收银 ¥68







