

POS-1519

Features:

Intel Celeron series and intel core I3 I5 processor for option

Hard Driver Msata SSD 64GB ,SSD 128GB and 256 GB for option

Multi-point projected capacitive touch panel

Optional side MSR and VFD220 customer display mounted to back cover

Ture flat and water-proof scratch-resistant surface display

Save shipping cost by dismounting the base plate to shrink the package if needed

Specification

Model	POS-1519
Name	15.1 inch all in one touch POS terminal
Housing	Platic shell machine body and aluminium base
Color	whole black color machine
Performance	
Main screen	15.1 inch touch screen monitor
Resoluiton	1024*768
Brightness	250cd/m ²
View angle	Horizon: 150; Vertical :140
Touch screen	Multi-point projected G+G capacitive touch
Sub-display	15 inch display W/o touch function for option
Customer display	2*20 VFD or 2*20 LCD display mounted to back cover for option
Motherboard	Intel Celeron Bay Trail J1900 2.0GHz, or Intel Celeron J4125,intel core I3 / I5 CPU for option
System Memory	1*SO-DIMM DDRIII slot, 4GB DDR3L/1333, 8GB for option
Storage device	Msata SSD 64GB or higer, up to 256GB
Audio	On board Real Tek ALC662
LAN	10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module
Operating System	Windows7/8/10, Embedded,WEPOS,Linux
Connectivity	
External I/O port J1900	power button*1,12V DC in Jack*1
	LAN:RJ-45*1
	USB*6
	15PIN D-sub VGA *1
	RS 232*2 line out*1,MIC in*1
Options	
MSR	optional side MSR
Package	
Weight	Net 6.5Kg, Gross 8.0Kg for single screen

Package with foam inside	425*275*405mm for single screen, 440*295*425mm for dual screen
Environment	
Operating temperature	0 to 40 degrees centigrade
Storage temperature	-10 to 60 degrees centigrade
Working humidity	10%~80% No condensation
Storage humidity	10%~90% No condensation
Accessories	
Power adapter	110-240V/50-60HZ AC power input ,DC12V/5A output adaptor
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available











**All in one
Touch POS system**