

# 17.1-inch Windows Touch Screen POS Terminal with Aluminium Alloy Base

(M/N:POS-1701)

## Features:

- 17-inch high brightness LCD screen;
- Multi-point projected capacitive touch panel;
- Removable bottom plate for smaller packaging and less shipping cost;
- The main screen supports 300° rotation to meet any observation angle;
- Borderless screen , the front protects against direct water splashes;
- Ultra-thin body makes the product more concise and stylish;
- Thick and stable aluminum base;
- Cable slots inside the base make the cable more tidy;
- Customer display, secondary screen and MSR installation position is reserved on the shell.

## Specification

Model	POS-1701
Name	17.1 inch touch POS terminal
Housing	Plastic shell and metal base
Color	Whole black or whole white coulor machine
<b>Display</b>	
Main screen	17.1 inch touch screen monitor
Resoluiton	1400*900
Brightness	200cd/m <sup>2</sup>
View angle	Horizon: 60; Vertical :90
Touch screen	Multi-point projected G+G capacitive touch
Customer display	2*20 VFD or 2*20 LCD display mounted to back cover for option
<b>Performance</b>	
Motherboard	Intel Celeron Bay Trail J1900 2.0GHz usually or intel core I3 / I5 4 <sup>th</sup> generation CPU for option
System Memory	1*SO-DIMM DDRIII slot, support1333*/1600 4GB usually ,2GB/8GB for option
Storage device	Msata SSD 64GB or higer, up to 256GB
Audio	On board Real Tek ALC662
LAN	10/100Mbps,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module
MSR	optional side MSR
Operating System	Windows7/8/10, Embedded,WEPOS,Linux
<b>Connectivity</b>	

External I/O port J1900 or I3 I5	Power button*1
	12V DC in jack*1
	LAN:RJ-45*1
	USB*6
	15PIN D-sub VGA *1
	HDMI*1, RS 232*1 for I3/I5
	RS232*2 for J1900
	line out*1,MIC in*1
<b>Package</b>	
Weight	Net 4.5Kg Gross 5.5 Kg
Package with foam inside	485*453*205 mm
<b>Environment</b>	
Operating temperature	0 to 40 degrees centigrade
Storage temperature	-10 to 60 degrees centigrade
Working humidity	10%~80% No condensation
Storage humidity	10%~90% No condensation
<b>Accessories</b>	
Power adapter	110-240V/50-60HZ AC power input ,DC12V/5A output adaptor
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available
<b>Other</b>	
Compliance	FCC Class A/CE Mark/LVD/CCC























