

# **POS-B11.6 high resolution pos system vending machine with thermal printer**

(M / N: POS-B11.6 )

## **Features:**

Elegant base B for pos machine.

Intel Celeron Processor J1900 Quad core CPU 2.0GHz high configuration for Windows system

8-cores ARM A83T 8-core ARM Cortex-A7 processor for Android system

2GB RAM + 8GB ROM standard (Android)

2 GB RAM + 32 GB standard SSD (Windows)

11.6-inch multi-point capacitive touch screen

11.6-inch non-touch secondary screen,

Built-in thermal printer of 58 mm or 80 mm (optional)

Built-in MSR RFID reader (optional)

Elegant display panel

## **applications:**

Catering: hotel, restaurant, fast-food restaurant, cafeteria, pastry shop and patisserie

Dealer: Business Street, boutiques, department store, cosmetics shop and high class barber shop

Recreation: sauna, spa, night club, theme park, casino and lottery ticket sales points

Commercial: information management terminals for parking, inn, aviation, subway, station and pier

## **Photo exhibition:**



**Parameter:**

|                     |  |
|---------------------|--|
| Template            | POS -B11.6   |
| Main board ①        | Intel Celeron J1900 Quad Core 2.0 GHz Processor (Windows)  |
| Main board②         | Processor Cortex-A7 8-core ARM A83T to 8 GHz (Android)   |
| OS①                 | Windows7 (Beta)  |
| OS②                 | Android 5.1  |
| Memory①             | 2 GB of RAM 32 GB SSD (Windows)  |
| Memory②             | 2GB RAM of 8GB RAM (Android)   |
| Touch screen        | Multipoint capacitive touch  |
| Screen size         | 11.6 inches, 16: 9   |
| Customer display    | LCD customer display (default),<br>Options: 11.6 inches without touch screen, VFD customer display, other scree size or non-customer display |
| Color               | Black or white   |
| Printer             | 58mm thermal gear printer or 80mm thermal printer with automatic cutter (Options)  |
| I / O Port (①J1900) | USB * 4  |
|                     | RJ45 * 1   |
|                     | RJ11 * 1 (optional)  |
|                     | VGA * 1  |
|                     | HDMI * 1 (for vice screen)   |
|                     | DB9 port RS232 * 1, (can add 2 ports for optional)   |

|                          |  |
|--------------------------|--|
| I / O Port (@A83T)       | RJ11 * 1 (Opional)   |
|                          | TF slot * 1  |
|                          | RJ45 * 1   |
|                          | HDMI * 1 (for vice screen)   |
|                          | USB * 2 (can add 4 ports for optional)                                       |
|                          | DB9 port RS232 * 1   |
|                          | Audio * 1  |
|                          | OTG USB port * 1   |
| Operating temperature    | 0 °C to 40 °C  |
| Other function (Android) | Bluetooth, WIFI  |
| Optional items (Windows) | RFID, MSR camera, 3G, DB25 parallel port, DB9 port RS232 * 3                 |
| Optional items (Android) | 3G, 4G camera, VFD, RFID, MSR, LCD display of other dimensions               |
| Storage temperature      | From -20 °C to 60 °C   |
| Packing size             | 46 * 43 * 51 centimeters   |
| Power adapter            | 110-240 V / 50-60 Hz AC power input, 12/24 V output depending on the printer |



POS-B11.6





POS-B11.6





POS-B11.6





POS-B11.6







## ▶ Company



## ► Certificates



## ► Payment



## ► Contact us



Richard Hu



## OCOM Technologies Limited

---

**Add:** 4/F, Block10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

**Tel:** 0086.755.8605.3207 ext 808

**Fax:** 0086.755.8605.3207 ext 868

**Web:** [www.ocominc.com](http://www.ocominc.com)

**E-mail:** [richard@ocominc.com](mailto:richard@ocominc.com), [richard@ocomtech.com.cn](mailto:richard@ocomtech.com.cn)

**Skype:** ocominc2000; **MSN:** ocomtech@hotmail.com

**Ali TM:** szocominc; **QQ:** 2485890637

**Mobile/Wechat/Whatsapp:** 0086. 133 5293 2860



Reliable One-Stop Supplier for POS and Auto-ID Related Products