

# **POS-B11.6 windows all in one touch screen pos system for retail store**

(M / N: POS-B11.6 )

## **Features:**

Elegant base B for pos machine.

Intel Celeron Processor J1900 Quad core CPU 2.0GHz high configuration for Windows system

8-cores ARM A83T 8-core ARM Cortex-A7 processor for Android system

2GB RAM + 8GB ROM standard (Android)

2 GB RAM + 32 GB standard SSD (Windows)

11.6-inch multi-point capacitive touch screen

11.6-inch non-touch secondary screen,

Built-in thermal printer of 58 mm or 80 mm (optional)

Built-in MSR RFID reader (optional)

Elegant display panel

## **applications:**

Catering: hotel, restaurant, fast-food restaurant, cafeteria, pastry shop and patisserie

Dealer: Business Street, boutiques, department store, cosmetics shop and high class barber shop

Recreation: sauna, spa, night club, theme park, casino and lottery ticket sales points

Commercial: information management terminals for parking, inn, aviation, subway, station and pier

## **Photo exhibition:**



**Parameter:**

Template	POS -B11.6
Main board ①	Intel Celeron J1900 Quad Core 2.0 GHz Processor (Windows)
Main board②	Processor Cortex-A7 8-core ARM A83T to 8 GHz (Android)
OS①	Windows7 (Beta)
OS②	Android 5.1
Memory①	2 GB of RAM 32 GB SSD (Windows)
Memory②	2GB RAM of 8GB RAM (Android)
Touch screen	Multipoint capacitive touch
Screen size	11.6 inches, 16: 9
Customer display	LCD customer display (default), Options: 11.6 inches without touch screen, VFD customer display, other scree size or non-customer display
Color	Black or white
Printer	58mm thermal gear printer or 80mm thermal printer with automatic cutter (Options)
I / O Port (①J1900)	USB * 4
	RJ45 * 1
	RJ11 * 1 (optional)
	VGA * 1
	HDMI * 1 (for vice screen)
	DB9 port RS232 * 1, (can add 2 ports for optional)

I / O Port (@A83T)	RJ11 * 1 (Opional)
	TF slot * 1
	RJ45 * 1
	HDMI * 1 (for vice screen)
	USB * 2 (can add 4 ports for optional)
	DB9 port RS232 * 1
	Audio * 1
	OTG USB port * 1
Operating temperature	0 °C to 40 °C
Other function (Android)	Bluetooth, WIFI
Optional items (Windows)	RFID, MSR camera, 3G, DB25 parallel port, DB9 port RS232 * 3
Optional items (Android)	3G, 4G camera, VFD, RFID, MSR, LCD display of other dimensions
Storage temperature	From -20 °C to 60 °C
Packing size	46 * 43 * 51 centimeters
Power adapter	110-240 V / 50-60 Hz AC power input, 12/24 V output depending on the printer



POS-B11.6





POS-B11.6





POS-B11.6





POS-B11.6





# POS-B11.6





## ▶ Company



## ► Certificates



## ► Payment



## ► Contact us



Richard Hu



## OCOM Technologies Limited

---

**Add:** 4/F, Block10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

**Tel:** 0086.755.8605.3207 ext 808

**Fax:** 0086.755.8605.3207 ext 868

**Web:** [www.ocominc.com](http://www.ocominc.com)

**E-mail:** [richard@ocominc.com](mailto:richard@ocominc.com), [richard@ocomtech.com.cn](mailto:richard@ocomtech.com.cn)

**Skype:** ocominc2000; **MSN:** [ocomtech@hotmail.com](mailto:ocomtech@hotmail.com)

**Ali TM:** szocominc; **QQ:** 2485890637

**Mobile/Wechat/Whatsapp:** 0086. 133 5293 2860



Reliable One-Stop Supplier for POS and Auto-ID Related Products