

China factory made J1900 32G SSD 15" all in one touch screen POS terminal price

(M/N:POS-C15)

Features:

- 1 Intel Celeron Processor J1900 Quad core 2.0GHz HighConfiguration CPU for Windows system
- 1 2.0GHz A83T ARM 8-Core Cortex-A7 Processor for Android system
- 1 2GB RAM+8GB ROM standard (Android)
- 1 2GB RAM+32GB SSD standard (Windows)
- 1 5 wire resistive touch screen(default),Capacitivescreen for optional
- 1 58/80mm embedded thermal printer for optional
- 1 Magnetic member card reader for optional
- 1 VFD customer display or vice screen

Applications:

- 1 Catering: hotel,restaurant, fast-food restaurant, coffee shop, bakery and cake shop
- 1 Retailer: Business Street,boutique, department store, cosmetics shop and high-class barbershop
- 1 Recreation: sauna, spa,night club, theme park, casino and point of sales for lottery ticket
- 1 Commercial: informationmanagement terminals for parking lot, inn, aviation, subway, station and wharf

Pictureshow:



Parameter

| | |
|-------------------|--|
| Model | POS-C15 |
| Color | Silver-gray or Black |
| CPU① | Intel Celeron J1900 Quad core 2.0 GHZ |
| CPU② | 2.0GHz A83T ARM 8-Core Cortex-A7 Processor |
| Memory① | DDRIII 1066/1333*1 2GB (default) (Windows) |
| Memory② | 2GB RAM 8GB ROM ①Android② |
| OS① | Windows7(Beta) |
| OS② | Android 5.1 |
| Hard Driver | SSD 32GB (default) (Windows) |
| LCD panel Size | 15 inch TFT LCD |
| Brightness | 350cd/m2 |
| Resolution | 1024*768(max) |
| Touch Screen | 5 wire resistive touch screen |
| Printer Parameter | Print Density 203dpi |
| | Printing Command ESC/POS |
| | Paper Roll Diameter 60mm |
| | Paper Width 58mm or 80mm |
| | Printing Speed 60mm/s or 150mm/s |
| | MCBF(life) 50km |

| | |
|------------------------|--|
| Other optinoal funtion | MSR/ VFD220 customer displaiy/ vice screen |
| View Angle | Horizon: 150; Vertical :140 |
| | 1* power button 12V DC in jack*1 |
| | HDMI*1 |
| | VGA(15Pin D-sub)*1 |
| I/O port□J1900□ | LAN:RJ-45*1 |
| | USB(2.0)*4 |
| | RS232*2 |
| | MIC IN*1 Audio out*1 |
| | RJ11*1 (Optional) |
| | TF slot *1 |
| I/O port□A83T□ | RJ45*1 |
| | HDMI for vice screen |
| | DB9 RS232 port*1□USB*2 |
| | Audio*1 |
| Operating temperature | 0°C to 40°C |
| Storage temperature | -20°Cto 60°C |
| Operating System | Windows XP above, Embedded,WEPOS,Linux |
| Power adapter | 110-240V/50-60HZ AC power, Input DC12/5A out put |