

# **(POS-H15)15.6 OR 15.1 INCH ALL IN ONE TOUCH POS Terminal**

(M / N: POS -H156W / A-H151W / A)



OCOM H Series pos Integrated High Speed Thermal Printer and Scanner Module Inside, IT IS A Kind of Cost-Effective Machine For Using, Different Frame Colors Make Machine More Beautiful,Extended I Interface Make a Few More External Devices Connected, Newly Designed Rear Cover Which Can Be Easily Removed Without Tools for Faster Installation and Maintenance.

## **Features:**

Intel Celeron Series and Intel Core i3 i5 Processor for option

RK3288 high speed RockChip processor

EMMC 8 GB / 16GB / 32 GB for option

MSATA SSD 64GB Hard Driver, SSD 128GB A 256 GB for option

58 mm high speed thermal printer and 80 mm integrated for option

Multi-point projected capacitive tactile panel

Optional side MSR and VFD220 display the customer's display mounted on the pos Teriore cover

Integrated bar-codes scanner for option

Surface true and water / resistant resistant resistant

**Specifications:**

Template	POS -H156	POS -H151
First name	15.6 INCH ALL IN ONE TOUCH SCREEN pos TERMINAL	15.1 INCH ALL IN ONE TOUCH SCREEN pos TERMINAL
Accommodation	Plastic with metal combined	
Color	White Machine Body or Black Machine Body Match Orange Or Blue Frame Colors	
Screen		
Main screen	15.6 Inch Touch Screen Monitor	15.1 inch Touch Screen Monitor
Resolution	1366 * 768	1024 * 768.
Brightness	250cd / m. <sup>2</sup> .	
Angle view	Horizon: 150; Vertical: 140	
Touch screen	Capacitive touch of multi-point G + G	
Under-es position	15.6 / 14 / 11.6 Inch Display w / or w / o Touch Function, Resolution 1366 * 768 for optional	15.1 Inch Display w / or w / o Touch Function, Resolution 1024 * 768
Customer display performance	2 * 20 VFD Mounted to Back Cover for Option	
Windows J1900	Motherboard	Intel Celeron Bay Trail J1900 2.0GHz or Intel Core i3 / i5 4 <sup>th</sup> Generation CPU for option
	System memory	1 * SO-DIMM DDRIII Slot, Support 1333 * / 1600 2GB / 4GB / 8GB FOR OPTION
	DISA pos IVI of storage	Msata SSD 64 GB or Higer, up to 256 GB
	Audio	ON BOARD REAL TEK ALC662 AUDIO CHIP
	LAN	10 / 100Mbps, Realtek RTL8111F LAN Chip Mini PCI-E Slot integrated, built-in WiFi module support
	Operating system	Windows7 / 8/10, Embedded, We POS, Linux

Android RK3288	Motherboard	Rockchip Series RK3288, Quad Core 1.8G, RK3399 for optional
	System memory	On Board Ddriii 2GB, 4GB for option
	DISA pos IVI of storage	On Board 16GB EMMC, 32GB for option
	Audio	ON BOARD REAL TEK ALC5640 AUDIO CHIP
	LAN	10 / 100Mbs, Realtek RTL8111F LAN Chip
	WiFi & BT Module	Support Wi-Fi 802.11b / g / n, BT3.0 / BT4.0 Support
	Operating system	Android 7.1
Connectivity		
Windows / Android (J1900 & RK3288)	Power button * 1	
	12V DC in Jack * 1	
	LAN: RJ-45 * 1	
	USB * 6	
	MIC IN * 1, AUDIO OUT * 1	
Windows (J1900)	Com (rs232) * 1 or hdmi * 1 for option	
	VGA (15pin D-Sub) * 1	
	RJ11 For Cash Drawer * 1 For Option	
Android (RK3288)	COM (RS232) * 1	
	On Board RJ11 For Cash Drawer * 1, RJ11 from Printer Port For Cash Drawer * 1 (Optional)	
	TF Card Slot * 1	
Options		
80mm Thermal Printer	Direct Thermal Printing	
	100mm / s Pringting Speed	
	79.5 - / + 0.5mm Paper Width and Printable Width 72mm	
	With Austo Cutter Function and Thermal Head Life 50km	
	LPT Communication	
58mm Thermal Printer	Direct Thermal Printing	
	85mm / s pringting speed	
	57.5 - / + 0.5mm Paper Width and Printable Width 48mm	
	Thermal Head Life 50km	
	LPT Communication	

MSR.	Optional side MSR.
web room	Web Room Mounted On Top of the Display For Option
Scanner	Support 1D & 2D Code-Scanning for Option
Speaker	4ohm / 5W Speakers Inside for option
Package	package
Weight	NET: 5.6kg, Gross: 7.7kg for 15.6 with15.6 Dual Screen / No Printer Built in
Pack with foam inside	340 * 450 * 480mm
2in1 carton	700 * 460 * 500mm / Gross: 17kg
Environment	
Operating temperature	0 to 40 degrees Celsius
Storage temperature	-10 at 60 degrees centigrade
Work humidity	10% ~ 80%
Storage humidity	10% ~ 90%
Accessories	
Power adapter	110-240V / 50-60Hz AC PowerInput, DC12 / 5A Output Adapter for w / o Printer and w / 58mm Printer Machine DC12V / 7A Out Put Adaptor Only for w / 80mm Printer Machine
Power cord	Power cord plug compatible with USA / EU / UK etc. And customized
CD Driver	Motherboard driver and touch drivers inside for the option
Other	
Conformity	FCC class A / CE / LVD / CCC class sign

More images of the products shown



No need for tools to remove the pos Temester cover, very comfortably for updating the RAM / SSD and customer maintenance



The side USB ports make the machine more easily upload and unload



Doors external



Package

