

21.5 Inch Windows/Android Self-Service POS System

(M/N:POS-K003)

Features:

- Top design in this kiosk industry, quick responses, run stably;
- Highly integrating multi-function, space-saving, easy to operate;
- Best shopping experience and improving the store image;
- Labor cost-saving;
- Time saving for the customers waiting at cashier front desk;
- High quality scanner make goods-scanning quickly;
- Support the payment of Wechat and Alipay;
- Support wall-mounting and standing alone.

Specification

Model	POS-K003-W	POS-K003-A
Name	21.5 inch all in one touch screen Kiosk	
Housing	plastic with metal combined	
Color	whole white color	
Display		
Main screen size	21.5 inch touch screen monitor	21.5 inch touch screen monitor
Resolution	1920*1080	1920*1080
colorBrightness	250cd/m2	
View angle	Horizon: 178; Vertical :178	
Touch screen	10-point projected G+G capacitive touch	
Performance		
Motherboard	Intel Celeron Bay Trail J1900 2.0GHz or intel core I3 / I5 4th generation CPU for option	ARM Cortex-A17 -RK 3288 quad core 1.8GHz CPU
System Memory	1*SO-DIMM DDRIII slot, support 1333*/1600 4GB	On board 2GB DDRIII
Storage device	Msata SSD 64GB	16GB eMMC
Audio	On board Real Tek ALC662 audio chip	On board Real Tek audio chip ALC5640
LAN	10/100Mbs, Realtek RTL8111F Lan chip	10M/100M, RTL8201F
WIFI	Support 802.11 a/b/g	Support 802.11 a/b/g
Speaker	Built in 8ohm/10watt speakers	
Camera	Face recognition for payment (option)	
Operating System	Windows 7/8/10, Embedded, WEPOS, Linux	Android 7.1
Connectivity		
External I/O port (J1900/RK3288)	Power switch*1	
	100V-240V 50HZ/60HZ AC power Socket*1	
	USB*2	
	LAN:RJ-45*1	
Scanning platform	package	
Light Source	Illumination: 617nm red LED	
Power supply	5V DC	
Support 1D	UPC, EAN, Code 128, Code 39, Code 93, Code 11, Interleaved 2 of 5, Matrix 2 of 5, Codabar, MSI Plessey, GS1 DataBar, China Postal, Korean Postal, etc....	
Support 2D	PDF417, Micro PDF417, Data Matrix, Maxicode, QR Code, Micro QR, Aztec, Hanxin, etc.....	
Barcode precision	4 mil code 39	

Barcode Sensitivity	Pitch:±60°@ 0°Roll and 0°Skew Roll:±360°@ 0°Pitchand0°Skew Skew:±65°@ 0°Roll and 0°Pitch
Prompt Mode	Buzzer
Interface	USB
Printer	
80mm thermal printer	Direct thermal printing
	150mm/s printing speed
	79.5-/+ 0.5mm paper width and printable width 72mm
	Auto cutter function
	Power DC 24V
	Resolution 203DPI
Environment	
Operating temperature	0 to 40 degrees centigrade
Storage temperature	-10 to 60 degrees centigrade
Working humidity	10%~80% No condensation
Storage humidity	10%~90% No condensation
Accessories	
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available
CD driver	Motherboard driver and touch driver inside (Option)
Other	
Compliance	FCC Class A/CE Mark/LVD/CCC



POS-K003





POS-K003





POS-K003





POS-K003





POS-K003



