

POS-M1162A/W 11.6 inch Android /Windows POS terminal With 80MM Thermal Receipt/Label
Printer For Options

(M/N:POS-M1162-W/POS-M1162-A)

Features:

Intel Celeron series and intel I3 I5 or RK3288 CPU for option
Hard Driver Msata SSD 64GB ,SSD 128GB an 256 GB for option
80mm high speed thermal printer built in
Multi-point projected capacitive touch panel
VFD220 customer display mounted to back cover
NFC card reader,bar-code scanner as option
Ture flat and water-proof scratch-resistant surface display

Specification

Model	POS-M1162-W	POS-M1162-A
Name	11.6inch all in one Windows touch screen pos terminal	11.6 inch all in one Android touch screen pos terminal
Housing	plastic with metal combined	
Color	Black and white color	
Display		
Main screen size	11.6 inch IPS touch screen monitor	11.6 inch IPS touch screen monitor
Resolution	1366*768,1920*1080 for option	1366*768,1920*1080 for option
Brightness	300cd/m ²	
View angle	Horizon: 160; Vertical :150	
Touch screen	multi-point projected G+G capacitive touch	
Vice screen	4.3inch lcd display ,resolution 800*480 for option	
Customer display	2*20 VFD mounted to back cover for option	
Performance		
Motherboard	Intel Celeron Bay Trail J4125 2.0GHz,intel core I3/I5 for option	ARM Cortex-A17 -RK 3288 quad core 1.8GHz CPU
System Memory	1*SO-DIMM DDRIV slot, 2133 Mhz 2GB/4GB 8GB for option	On board 2GB DDRIII
Storage device	Msata SSD 64GB or higer, up to 256GB	16GB eMMC,support 32GB TF card expanded for option
Audio	On board Real Tek ALC662 audio chip	On board Real Tek audio chip ALC5640
LAN	10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module	10M/100M RTL8201F,10M/100M/1000M RTL8211E for option
Operating System	Windows7/8/10, Embedded,WEPOS,Linux	Android 7.1 and Anroid 8.1

Connectivity		
External I/O port(J4125/RK3288)	power button*1	
	12V DC in jack*1	
	COM(RS232) * 1	
	LAN:RJ-45*1	
	USB *5	
	RJ11 for Cash drawer *1	
	VGA(15Pin D-sub)*1	TF card slot*1,SIM slot*1
	MIC in*1 Audio out*1	RJ11*1
Options		
80mm thermal printer	direct thermal printing,support label and receipt	
	200mm/s printing speed	
	79.5-/+ 0.5mm paper width and printable width 72mm	
	with auto cutter function and thermal head life 100km	
speaker	8ohm/3W speaker	
WIFI	IEEE 802.11 a/b/g/n	
communication	3G/4G	
NFC card reader	ISO14443TypeA	
scanner	1D/2D barcode decoding	
camera	5.0MP/Auto focus,support 1D/2D	
Battery	6000mAh large capacity battery	
Package		
Weight	Net 3.1Kg Gross 3.8Kg	
Package with foam inside	180*370*380mm	
2 in 1 carton	370*365*392/12kg	
Environment		
Operating temperature	0 to 40 degrees centigrade	
Storage temperature	-10 to 60 degrees centigrade	
Working humidity	10%~80% No condensation	
Storage humidity	10%~90% No condensation	
Accessories		
Power adapter	110-240V/50-60HZ AC powerinput ,DC12/7A output adaptor	
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available	
CD driver	Motherboard driver and touch driver inside	
Other		
Compliance	FCC Class A/CE Mark/LVD/CCC	

























11.6 inch Touch Screen Computer System
Model: POS-M1162
Configuration: i1900+GBRAM+4SSD+NFC+Display
80MM Printer+2D Scanner
Power Input: DC 12V 7A
Barcode: POSM1162213820001
Made in China
CE FC

