(M/N:POS-M1162-W/POS-M1162-A)

## **Features:**

Intel Celeron series and intel I3 I5 or RK3288 CPU for option Hard Driver Msata SSD 64GB ,SSD 128GB an 256 GB for option 80mm high speed thermal printer built in Multi-point projected capacitive touch panel VFD220 customer display mounted to back cover NFC card reader,bar-code scanner as option Ture flat and water-proof scratch-resistant surface display

## **Specification**

Model	POS-M1162-W	POS-M1162-A
Name	11.6inch all in	11.6 inch all in
	one Windows touch screen	one Android touch screen
	pos terminal	pos terminal
Housing	plastic with metal combined	
Color	Black and white color	
Display		
Main screen size	11.6 inch IPS touch screen	11.6 inch IPS touch screen
	monitor	monitor
Resolution	1366*768,1920*1080 for	1366*768,1920*1080 for
	option	option
Brightness	2	
	300cd/m	
View angle	Horizon: 160; Vertical :150	
Touch screen	multi-point projected G+G capacitive touch	
Vice screen	4.3inch lcd display ,resolution 800*480 for option	
Customer display	2*20 VFD mounted to back cover for option	
Performance		
Motherboard	Intel Celeron Bay Trail	ARM Cortex-A17 -RK 3288
	J4125 2.0GHz,intel core	quad core 1.8GHz CPU
	13/I5 for option	'
	'	
System Memory	1*SO-DIMM DDRIV	On board 2GB DDRIII
, ,	slot, 2133 Mhz 2GB/4GB	
	8GB for option	
Storage device	Msata SSD 64GB or higer,	16GB eMMC,support 32GB
	up to 256GB	TF card expanded for option
Audio	On board Real Tek ALC662	On board Real Tek audio
	audio chip	chip ALC5640
LAN	10/100Mbs,Realtek	10M/100M
2	RTL8111F Lan chip	RTL8201F,10M/100M/1000M
	built in Mini PCI-E	RTL8211E for option
	slot,support embedded	
	WIFI module	
Operating System	Windows7/8/10,	
Sperdening System	Embedded, WEPOS, Linux	Android 7.1 and Anroid 8.1
	Lindeadea, Wei OS, Linax	, and old fill dild fall old old
	1	

Connectivity		
	power button*1	
	12V DC in jack*1	
External I/O		
port(J4125/RK3288)	LAN:RI-45*1	
	USB *5	
	RJ11 for Cash drawer *1	
	VGA(15Pin D-sub)*1	
	MIC in*1 Audio out*1 RJ11*1	
Options	I I I I I I I I I I I I I I I I I I I	
80mm thermal printer	r direct thermal printing, support label and receipt	
domini tricimai printer	200mm/s pringting speed	
	79.5-/+ 0.5mm paper width and printable width 72mm	
	with atuo cutter function and thermal head life 100km	
speaker	8ohm/3W speaker	
WIFI	IEEE 802.11 a/b/g/n	
comunication	3G/4G	
NFC card reader	ISO14443TypeA	
scanner	1D/2D barcode decoding	
	5.0MP/Auto focus,support 1D/2D	
Camera	· ·	
Battery	6000mAh large capacity battery	
Package	Not 2 1kg Cross 2 9kg	
Weight	Net 3.1Kg Gross 3.8Kg	
Package with foam inside	180*370*380mm	
2 in 1 carton	370*365*392/12kg	
Environment		
Operating temperature	0 to 40 degrees centigrade	
Storage temperature	-10 to 60 degrees centigrade	
Working humidity	10%~80% No condensation	
Storage humidity	10%~90% No condensation	
Accessories		
Power adapter	110-240V/50-60HZ AC powerinput ,DC12/7A output	
	adaptor	
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available	
CD driver	Motherboard driver and touch driver inside	
Other		
Compliance	FCC Class A/CE Mark/LVD/CCC	















































