

10.1 Inch Windows or Android Price Checker

(M/N:OCPC-001-W/OCPC-001-A)

OCOM 001 price checker has fashionable and elegant appearance,it can be installed Windows or Android OS for choosing,easy operation for the customers price checking before buying.tablet like touch screen can be mounted to wall or any other VESA standard brackets.

Features:

1. Intel Celeron series
2. Hard Driver Msata SSD 64GB ,SSD 128GB and 256 GB for optionn
3. Ture flat and water-proof scratch-resistant surface display

Specification

| | | |
|----------------------|--|---|
| Model | OCPC-001-W | OCPC-001-A |
| Name | 10.1 inch all in one touch screen machine | 10.1 inch all in one touch screen machine |
| Housing | plastic with metal combined | |
| Color | wholeblack machine body | |
| Display | | |
| Main screen size | 10.1 inch touch screen monitor | 10.1 inch touch screen monitor |
| Resolution | 1280*800 | 1280*800 |
| Brightness | 250cd/m ² | |
| View angle | Horizon: 160; Vertical :150 | |
| Touch screen | multi-point projected G+G capacitive touch | |
| Performance | | |
| Motherboard | Intel Celeron Bay Trail J1900 2.0GHz | Rockchip series RK3288 ,quad core 1.8G,A63 CPU for option |
| System Memory | 1*SO-DIMM DDRIII slot, support1333*/1600 4GB | On board 2GB DDRIII |
| Storage device | Msata SSD 64GB | 16GB eMMC |
| Audio | On board Real Tek ALC662 audio chip | On board Real Tek audio chip ALC5640 |
| LAN | 10/100 Mbs, Realtek RTL8111F Lan chip | WIFI/802.11/b/g/n |
| Operating System | Windows 7/8/10, Embedded,WEPOS, Linux | Up to Android 8.1 (Android 7.1 for A63) |
| scanner | Bar-code scanner inbuilt | |
| Connectivity | | |
| External port(J1900) | I/O | power button*1, 12V DC in jack*1 |
| | | LAN:RJ-45*1 |
| | | RS232*1 |
| | | USB *4 |
| | | Audio out*1 |

| | | |
|--------------------------|--|----------------------------------|
| External port(RK3288) | I/O | power button*1, 12V DC in jack*1 |
| | | LAN:RJ-45*1 |
| | | HDMI*1 |
| | | USB *2 |
| | | SIM slot*1, SD card slot*1 |
| | | Audio out*1 |
| External port(A63) | I/O | power button*1, 12V DC in jack*1 |
| | | LAN:RJ-45*1 |
| | | USB *4 |
| | | SD card slot*1 |
| | | Audio out*1 |
| Package | | |
| Weight | Net 1.5Kg Gross 3.0Kg | |
| Package with foam inside | 360*290*180mm | |
| Environment | | |
| Operating temperature | 0 to 40 degrees centigrade | |
| Storage temperature | -10 to 60 degrees centigrade | |
| Working humidity | 10%~80% No condensation | |
| Storage humidity | 10%~90% No condensation | |
| Accessories | | |
| Power adapter | 110-240V/50-60HZ AC power input ,DC12V/5A output | |
| Power cable | Power cable plug compatible with USA /EU / UK etc and customized available | |
| Other | | |
| Compliance | FCC Class A/CE Mark/LVD/CCC | |













