Handheld Android POS Terminal with payment function (M/N: POS-T8) Android 4.4 operation system. Adopts Qualcomm quad-core 1.2GHz processor. 4.0 inches IPS capacitive touch screen. Safety and reliable design Passed Unionpay Pboc L1& L2; passed PIN input safety certification. Unionpay direct connect POS network access. Support Printing Receipt and Barcode reading Supports magnetic stripe card, IC card, contactless card.

	Supports magnetic stripe card, IC card, contactless card.
System Parameters	
CPU	Qualcomm quad-core 1.2GHz
OS	Android 4.4
RAM/ROM	ROM 4GB eMMC; RAM 512MB/1GB DDR2;
	support external micro SD card, 32 GB at most
Display	4.0 inch capacitive, multi touch; 480*800, IPS display
Keypad	3 Touch System Keys, 15 physical keys (include Power key, Custom key, POS Cipher key and Command key)
Battery	Lithium polymer battery, 4000mAh
Functional Configuration	·
Camera	Rear Camera 5M AF (support flashlight), Front Camera 0.3M wide angle
Printer	Built-in 2 inches thermal printer
Navigation	Built-in GPS, support AGPS
Indicator Light	System indicator light, POS indicator light
Audios	Built-in speaker, buzzer, microphone, vibrator
Sensors	Gravity sensor
POS	·
Sound Wave Payment	Support
Magnetic Strip Card	Triple track MSR, bi-directional swiping ISO7811, 7812
IC Card	1 Solt, Support 1.8V/3V/5V, ISO7816, PBOC and EMV
Contactless card	13.56MHz, ISO/IEC 14443 Type A/B, qPBOC
SAM Card	1 SAM Solt, ISO7816
Cipher Keyboard	Built-in keypad
Network Parameters	
Network Type	WCDMA/GSM
Network Spectrum	WCDM 2100MHz
	GSM/GPRS/EDGE 850/900/1800/1900MHz
WLAN	802.11 a/b/g/n Bullt-in Antenna
Voice/Data Service	Support
WPAN	Slipeton V4.0 + EDR
External Interface	bidetooti 144.0 % EDN
USB Interface	Micro USB2.0, support USB OTG
Charger Jack	PICLE O SB2.0, Support USB OTG
Power Supply Jack	Pogo Pin, SV500mA
Communication	- годо гит, луч-зоотия
Physical Parameters	038, 63232
	horaca u a como Como Wa como D
Dimensions	205mm H * 82mm/67mm W * 33mm D
Weight	500g (battery included) -20°C ~ 60°C
Operating Temp	
Storage Temp	40°C = 80°C
Humidity	10%-90% RH non-condensing
Drop Test	1.0-meter drop protection
Roller Drop Test	500 times
ESD protection	±8KV contact discharge; ±15KV air discharge
Development Environment	
System Environment	Android 4.4/SP-UI
Development Environment	SDK
Management Software	PC management suite/MDM