

|                               |  |
|-------------------------------|--|
| Model                         | OCBP-402DT   |
| Material                      | Plastic housing  |
| Interface                     | USB,USB+Bluetooth,USB+Bluetooth +WIFI, USB+LAN   |
| Processor                     | 32 bit CPU   |
| Memory                        | 4MB Flash Memory,320KB RAM   |
| Printer Head life             | 50Km   |
| Power supply                  | Input□AC 100V-240V,50-60Hz,Output□DC 24V/2.5A  |
| Accessories                   | Power adapter,Power cable,USB cable,Manual, outside bracket for option   |
| Sensors                       | Label edge detection, Out of paper detection, Gap detection, Black mark detection,Cover-open detection   |
| Gap height                    | 2mm Min  |
| Black-mark height             | 2mm Min  |
| Font and bar-code rotation    | 0°,90°,180°,270°   |
| Compatible command            | TSPL   |
| <b>Printing</b>               |  |
| Printing method               | Direct Thermal   |
| Resolution                    | 203 DPI  |
| Printing speed                | 152mm /s Max   |
| Printing width                | 30-108mm   |
| Printing length               | 10-250mm   |
| <b>Barcode</b>                |  |
| Bar-code                      | 1D bar code:<br>Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Coda bar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST<br>2D bar code:PDF417, Maxi code, Data Matrix, QR code |
| Font                          | 8 alpha-numeric bitmap fonts,<br>Windows fonts are downloadable from software  |
| <b>Media</b>                  |  |
| Paper type                    | Folded paper or roll paper, die-cut label, black mark paper  |
| Paper width                   | 30-118mm   |
| Media thickness               | 0.06 ~ 0.22mm  |
| <b>Physical</b>               |  |
| Dimension                     | 220*112*102mm  |
| Weight                        | Net: 1.02kg  |
| Package box                   | 248*140*170mm/1.87Kg   |
| 8 in 1 carton                 | 516*300*360mm /12.4kg  |
| <b>Environment</b>            |  |
| Working temperature& humidity | 0 to 45 degrees centigrade, 10%~80% No condensation  |
| Storage temperature& humidity | -20 to 60 degrees centigrade , 10%~90% No condensation   |