

## Pos Bar code bar reader for 1D bar code (Model: OCBS-LA06 )

### Features:

#### barcode reader,bar code reader,code bar reader

- With auto-induction and auto-scanning function, green design;
- High scan rate and long reading distance;
- Excellent decode capability;
- KBW, RS232 and USB supported;
- Stand available;
- Durable construction combined with future-proofing;

### Specification:

#### barcode reader,bar code reader,code bar reader

| <b>Performance Characteristics</b> |  |
|------------------------------------|--|
| Light Source:                      | Visible laser (650-670nm)  |
| Scan Rate:                         | 100 scans per second   |
| Reading Distance                   | 2.5 ~600mm (100% UPC/EAN)  |
| Scanner Type:                      | Bi-directional   |
| Resolution:                        | 0.10mm (4mil) at PCS 0.9   |
| Print Contrast Minimum:            | 20%, minimum reflective difference (@650nm)  |
| Decode Capability:                 | UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5... |
| <b>Physical Characteristics</b>    |  |
| Interfaces Supported:              | PS2, RS232, USB  |
| Voltage:                           | DC+5V+/-5%   |
| Current:                           | 100 mA   |
| Idle Current:                      | <40 mA   |
| Power Source:                      | Host power or external (RS232) power supply  |
| Scanning Angle                     | Inclination 45° Elevation 60°  |
| Dimensions:                        | L165.42mm X W69.72mm X H89.67mm  |
| Weight:                            | 140g (without stand)   |
| Stand                              | With   |
| Color:                             | Ivory and black  |
| <b>User Environment</b>            |  |
| Operating Temperature:             | 0degree C~50degree C   |
| Storage Temperature:               | -40degree C~ 70degree C  |

|                          |  |
|--------------------------|--|
| Humidity:                | 5~95% relative humidity, non-condensing                          |
| Electrostatic Discharge: | Confirm to +/-15KV air discharge and +/-8KV of contact discharge |
| Drop Specifications:     | Withstands multiple 1.5m drops to concrete                       |
| <b>Safe:</b>             |  |
| EMI/RFI:                 | FCC Class A and CE   |
| Laser Safety:            | CDRH class 2 laser product                                       |

**Product Details:**

barcode reader, bar code reader, code bar reader



**Relevant documents:**

Do you want to know more product information? [Please Click here.](#)

Specification

User's Manual