

## 15-inch Touch POS terminal

(M/N:POS-8618)


### Features:

- l Intel Celeron 1037U dual core 1.8GHZ
- l Hard Driver SSD 32GB (default),SSD 64GB and HDD320G for optional
- l 5 wire resistive touch screen(default),Capacitive screen for optional
- l Card reader and VFD customer display for optional
- l I/O Interface Panel is hidden

### Applications:

- l Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop
- l Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop
- l Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket
- l Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

### Picture show:



### Parameter:

|                      |                                      |
|----------------------|--------------------------------------|
| Model                | POS8618                              |
| Optional Color       | Black or White                       |
| Optional Peripherals | VFD220E                              |
| Main Board           | Intel Celeron Processor              |
| CPU                  | Intel Celeron 1037U dual core 1.8GHZ |
| Chipset              | Intel NM70                           |
| Memory Support       | DDRIII 1066/1333*1 2GB (default)     |
| Hard Driver          | SSD 32GB (default)                   |
| LCD panel Size       | 15 inch TFT LCD                      |

|                           |  |
|---------------------------|--|
| Brightness                | 350cd/m <sup>2</sup>                             |
| Resolution                | 1024*768(max)                                    |
| Touch Screen              | 5 wire resistive touch screen                    |
| View Angle                | Horizon: 150; Vertical :140                      |
| I/O port                  | 1* power button 12V DC in jack*1                 |
|                           | PS2KB/MS*1                                       |
|                           | Serial*1 DB9 male                                |
|                           | Parallel:1*DB25 Parallel port                    |
|                           | VGA(15Pin D-sub)*1                               |
|                           | LAN:RJ-45*1                                      |
|                           | USB(2.0)*6                                       |
|                           | Audio out*1                                      |
|                           | MIC IN*1   |
| Operating temperature     | 0°C to 40°C                                      |
| Storage temperature       | -20°Cto 60°C                                     |
| Compliance                | FCC Class A/CE Mark/LVD/CCC                      |
| Packing dimension/ Weight | 410*310*410mm / 7.6 Kgs                          |
| Operating System          | Windows XP above, Embedded,WEPOS,Linux           |
| Power adapter             | 110-240V/50-60HZ AC power, Input DC12/5A out put |