

# HandHeld 2D Wireless Barcode Scanner

(M/N:OCBS-W239)



## Features:

- l. 2.4G or 2.4G +Bluetooth for option
- m. 300,000 pixel and global exposure high precision scanning engine
- n. Low power design can scan 20,000 times
- o. Scanning high density barcode has high performance
- p. Superior performance for Small two-dimensional codes
- q. Cradle is for charging and receiving

## Specification

<b>General</b>	
Model	OCBS-W239
Wireless function	2.4G or 2.4G+Bluetooth for option
Battery	3.7V/2500mAh (20000 times scan and transmission)
Prompting Mode	LED / buzzer
Working Voltage	+4.2V±10% VDC
Working current	226mA
Starting Current	204mA
Standby current	96mA
Shock Specifications	Designed to withstand 1.5m drops
<b>Performance</b>	
Illumination	White LED
Aiming	Red LED
Image sensor	CMOS
Image resolution	640*480
Print contrast	≥ 20% minimum reflective difference
scan angle	Roll/Pitch/Yaw:65°Yaw,65°Pitch,360°Roll
Decoding ability	1D :Codabar,Code 39,Code 32 Pharmaceutical (PARAF),Interleaved 2 of 5,NEC 2 of 5,Code 93,Straight 2 of 5 Industrial,Straight 2 of 5 IATA,Matrix 2 of 5,Code 11,Code 128,GS1-128,UPC-A,UPC-E,EAN/JAN-8,EAN/JAN-13, MSI,GS1 DataBar Omnidirectional,GS1 DataBar Limited,GS1 DataBar Expanded,China Post(Hong Kong 2 of 5),Korea Post 2D:Codeblock A,Codeblock F,PDF417,Micro PDF417,GS1 Composite Codes,QR Code,Data Matrix,MaxiCode,Aztec,HANXIN
Depth of scan field	Code 39 (4 mil) : 6 - 15 cm , Code39(5mil): 4 - 20cm, Code39(13mil): 6 - 35cm QR(15mil): 4 - 20cm, QR(20mil): 3 - 25cm, QR(30mil): 3 - 35cm UPC-A(13mil): 4 - 35cm, ENA-13(5mil): 6 - 15cm, ENA-13(5mil): 3 - 35cm
<b>Physical</b>	
Weight	Gross:290g
Package	122*165*105mm/493g
30 in 1 carton	525*430*360mm/16.5kg
<b>Environment</b>	
Working temperature& humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade , 10%~90% No condensation









