

VFD220B 40 20 columns 2 lines VFD Customer Display(M/N:VFD220B)

Features:

Supports 11 command modes included EPSON etc.

Power supply from 5V to 24V to prevent any mindless use of improper power input.

20-column x 2-line dot matrix in a wide viewing angle.

Easy connectivity to a wide range of POS products.

OPOS/JPOS driver is standard.

Specification

General	Display Method	Vacuum Fluorescent Display (Blue-green)
	Number of characters	40(20 columns x 2 lines)
	Brightness	500-1000 cd/m2
	Character font	5 x 7 dot matrix
	Character type	95 Alphanumeric, 32 International Characters
	Character size	9.02(H) x 5.25(W) mm
	Dot Size (X x Y)	0.86 x 1.05mm
	Download characters	9 characters
	Panel Dimension	200(W) x 77.5(D) x31(H)mm
	Pole Dimension	Per support length: 140(L) x 34.5(Dia)mm
	Base Dimension	169.5(W) x98.5(D) x39(H)mm
	Viewing Angle	Max. 90°
	Horizontal Rotation	Max. 355°
	Weight	Approx. 980 grams
Commands Mode		LD220, EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL
Language Support		FRANCE[]GERMANY[]U.K.[]DENMARK[]SWEDEN[]ITALY[]SPAIN[]JAPAN[]NORWAY[]DENMARKII[]SLAVONIC[]RUSSIA[]Portuguese[]Canadian French[]Nordic[]Turkish[]Greek[]West European Latin
Interface		RS-232(serial) / USB
Connection	Baud rate	Direct connection 9600 or 19,200 bps
Reliability	MTBF	30,000 hours
Power	Consumption	5~24 VDC
Safety	EMC standards	FCC, CE
	Safety standards	



Contact: Harold Hu

OCOM Technologies Limited

Address: 4/F, Block 10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China;

Website: www.ocominc.com, www.possolution.com.cn ;

E-mail: sales14@ocominc.com ;

Skype: [sales14@ocominc.com](https://www.skype.com/people/sales14@ocominc.com)

MSN: ocomsales14@hotmail.com ;

Whatsapp: 86.18948789890;

Wechat: 18948789890(ocomsales14);

Mobile: 86.18948789890;

QQ: 1467261417;

Tel: 0086.755.86053207-814;

Fax: 0086.755.86053207-868.