

VFD220D 20 columns 2 lines dot matrix in a wide viewing angle Customer Display

Features

- * Supports 11 command modes included EPSON etc.
- * Power supply from 5V to 24V to prevent any mindless use of improper power input.
- * 20-column x 2-line dot matrix in a wide viewing angle.
- * Easy connectivity to a wide range of POS products.
- * OPOS/JPOS driver is standard.

Specification

General	Display Method	Vacuum Fluorescent Display (Blue-green)
	Number of characters	40(20 columns x 2 lines)
	Brightness	500~1000 cd/m ²
	Character font	5 x 7 dot matrix
	Character type	95 Alphanumeric, 32 International Characters
	Character size	5.25 (W) x 9.02 (H)mm
	Dot Size (X x Y)	0.86 x 1.05mm
	Download characters	9 characters
	Panel Dimension	220(W) x 45(D) x 125(H)mm
	Pole Dimension	Per support length: 140(L) x 34.5(Dia)mm
Base Dimension	205(W) x 106(D) x 33(H)mm	
Viewing Angle	Max. 90°	
Horizontal Rotation	Max. 355°	
Weight	Approx. 980 grams	
Commands Mode	LD220, EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL	
Language Support	FRANCE[]GERMANY[]U.K[]DENMARKI[]SWEDEN[]ITALY[]SPAIN[]JAPAN[]NORWAY[]DEN MARKII[]SLAVONIC[]RUSSIA[]Portuguese[]Canadian French[]Nordic[]Turkish[]Greek[]Wes t European Latin	
Interface	RS-232(serial) / USB	
Connection	Baud rate	Direct connection 9600 or 19,200 bps
Reliability	MTBF	30,000 hours
Power	Consumption	5~24 VDC
Safety	EMC standards	FCC, CE
	Safety standards	



Contact: Harold Hu

OCOM Technologies Limited

Address: 4/F, Block 10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China;

Website: www.ocominc.com, www.possolution.com.cn ;

E-mail: sales14@ocominc.com ;

Skype: [sales14@ocominc.com](https://www.skype.com/people/sales14@ocominc.com)

MSN: ocomsales14@hotmail.com ;

Whatsapp: 86.18948789890;

Wechat: 18948789890(ocomsales14);

Mobile: 86.18948789890;

QQ: 1467261417;

Tel: 0086.755.86053207-814;

Fax: 0086.755.86053207-868.

