

Display

- * Supports 11 command modes included EPSON etc.
- * Power supply from 5V to 24V to prevent any mindless use of improper power input.
- * 20-column x 2-line dot matrix in a wide viewing angle.
- * Easy connectivity to a wide range of POS products.
- * OPOS/JPOS driver is standard.

Specification

| | | |
|------------------|---|--|
| General | Display Method | Vacuum Fluorescent Display (Blue-green) |
| | Number of characters | 40(20 columns x 2 lines) |
| | Brightness | 500~1000 cd/m ² |
| | Character font | 5 x 7 dot matrix |
| | Character type | 95 Alphanumeric, 32 International Characters |
| | Character size | 5.25 (W) x 9.02 (H)mm |
| | Dot Size (X x Y) | 0.86 x 1.05mm |
| | Download characters | 9 characters |
| | Panel Dimension | 220(W) x 45(D) x 125(H)mm |
| | Pole Dimension | Per support length: 140(L) x 34.5(Dia)mm |
| | Base Dimension | 205(W) x 106(D) x 33(H)mm |
| | Viewing Angle | Max. 90° |
| | Horizontal Rotation | Max. 355° |
| Weight | Approx. 980 grams | |
| Commands Mode | LD220, EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL | |
| Language Support | FRANCE □ GERMANY □ U.K □ DENMARK □ SWEDEN □ ITALY □ SPAIN □ JAPAN □ NORWAY □ DENMARK II □ SLAVONIC □ RUSSIA □ Portuguese □ Canadian French □ Nordic □ Turkish □ Greek □ West European Latin | |
| Interface | RS-232(serial) / USB | |
| Connection | Baud rate | Direct connection 9600 or 19,200 bps |
| Reliability | MTBF | 30,000 hours |
| Power | Consumption | 5~24 VDC |
| Safety | EMC standards | FCC, CE |
| | Safety standards | |

