## **SPECIFICATIONS:**

FECIFICATIONS.	
PHYSICAL CHARACTERSTICS	
Light Source:	Visible Red Laser 650 nm
Scanner Dimensions:	160mm * 70mm * 40mm(W * H * D)
Weight :	300G
Material:	ABS + PC
Scanning Mode:	One line scanning; Manual / Automatic
Indicator Way:	Buzzer and Indicator Light
PERFORMANCE CHARACTERSTICS	
Width of Scan Field:	20mm@scanner window
	260mm@260mm
Depth of Scan Field:	4mil (0.1mm)/5-60mm
	5mil (0.12mm)/10-100mm
	10mil (0.25mm)/15-250mm
	35mil (0.89mm)/140-600mm
	43mil (1.1mm)/150-800mm
Scan Speed:	120 scans/sec
Scan Precision:	0.10mm (pcs0.9)
Printing Contrast:	Minimum 30% reflection difference
Error Rate:	1/(6million)
Decode Capability:	International general 1D barcodes
Current:	60mA (working); ≦5uA(standby)
Scanning Corner:	32°
Scanning Elevation:	68°
Scanning Angle of Avertence:	52°
Working Frequency:	2.4GHz
Communication Distance:	100m (Open Places)
	20m (Indoor)
Communication Interface:	USB
USER ENVIRONMENT CHARACTERSTICS	
Drop Specification:	2m free fall
Laser Level:	Level-1 laser safety standard
Charge Power:	DC5V

## **Product Details:**

x x x x x x x x x

## **Relevant documents:**

Do you want to know more product information?Please Click here.

Specification