

Handheld payment touch pos terminal with wifi,4G,MSR,camera,bluetooth

(M/N:POS-Z90)

Feature:

- | Android 5.1 operating system
- | 5.0 inch screen touch
- | Long standby battery capacity is 3600 mAh
- | 58mm thermal printer
- | 5 million pixels camera
- | 2G /3G/4G wifi, bluetooth communication,
- | Integrated magnetic card reader,induction ICard reader and contact IC card reader
- | Passed the EMV L1 L2 and PBOC bank paymentcertification
- | Thecradle can be used for communication, charging, power bank,and providingwireless network (Optional)

Application :

applychain supermarkets, restaurants, convenience stores, clothing store, premises,bakery, cashier, pay, enters sells saves the business management function.

TechnicalSpecification:

Basic Information

Operating system	Android 5.1
RAM	RAM:1GB
Extended stored	FLASH:8GB
Display screen	5.0 inch
Touch screen	Capacitive touch screen, support the electronic signature
Battery	Lithium battery 3600 mah, 3.7 V
Bluetooth	Bluetooth 4.0
Camera	5 mega-pixel camera
Positioning function	GPS AGPS WLAN for Positioning
Printer	58mm thermal printer 30mm diameter Paper roll
Interface	Micro USB

POS Function

Magnetic card reader	Full track magnetic card reader Support ISO1788/7812,AAMVA protocol
IC card read-write	Support ISO7816 protocol
Non-contact card reader	Support ISO/IEC 14443 Type A&B, Mifare, felica card, in line with the EMV/PBOC PAYPASS specification
PSAM Card	Bank security payment chip card
Certification	Unionpay card acceptance terminal network detection EMV/PBOC3.0 L1 and L2 certification EMV/qPBOC3.0 L1 and L2 certification Unionpay intelligent safety standards point-of-saleterminals

Network Parameters

Network Type	GSM,WCDMA,TD-SCDMA,FDD-LET,TDD-LTE
--------------	------------------------------------

Network Spectrum	GSM850/900/1800/1900 WCDMA2100/1900/900/850 TD-SCDMA B34/B39 FDD-LTE B1/B2/B3/B4/B5/B7/B8/B20 TDD-LTE B38/B39/B40/B41
WLAN	IEEE802.11.b/n/g
Physical Parameters	
Size	191mm×80mm×46mm
Weight	650g
Operating Temp	-20°C ~ 60°C
Storage Temp	-40°C ~ 80°C
Humidity	10%~90% RH non-condensing

Pics:





POS-Z90



www.ocominc.com

CE FCC

