

cheap 58mm thermal POS bill receipt printer with big paper holder (OCP-587)

Product performance:

Appearance compact design, fashion technology;
 Easy paper feed structure, simple and convenient operation;
 High reliability of large motor and large gear movement;
 130 mm / s speed print, significantly improve the printing efficiency;
 Big paper warehouse design, the perfect support for 83MM large diameter rolls;
 Rich interface optional: USB, COM, Internet (100M), WIFI, Bluetooth, GPRS;
 Support GB18030 large font and multi language ;
 Supports LOGO and graphics downloads and print;
 Supports Windows, Linux, Android and IOS system print;
 100M Ethernet interface, print quickly while avoiding losing bills.

Specification:

Items	Parameters	
Print parameters	Printing Method	Thermal Line
	Printing Method	48MM
	Resolution	384dots/Line□8dots/mm□203dpi□
	Printing Speed	130mm/Second
	Interface Type	USB□COM□Internet□100M□WIFI□GPRS□Bluetooth
	Line Spacing	3.75 mm□Can adjust line spacing by command□
	Line No.	Font A:32 character /Line Font B:42 character/Line Simple,traditional Chinese-16 lines
	Character	Standard GB18030 simplified / traditional Chinese Fonts
	Character Size	ANKcharacter□Font A□1.5×3.0mm□12×24□ Font B□1.1×2.1mm□9×17□ Simplified/Traditional Chinese□3.0×3.0mm(24×24 Dots□
Bar code Character	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope /Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852 /PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/ ThaiVietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151, 1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	Bar code	1D bar code□UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/ CODABAR/CODE93/CODE128 2D bar code□QRCODE
Graphics printing	Supports bitmap download and print	

Paper	Type	Thermal Roll
	Width	57.5±0.5mm
	Diameter	≤83mm
	Feed Method	Easy feed(Clameshell feed)
Print commands	Commands	ESC/POS
Power	Power Adaptor	Input□AC 100V-240V,50-60Hz Output□DC 12V/2A
	Casher Drawer output	DC 12V/1A
Buffer	Input Buffer	4K
	NV Flash	40K
physical characteristics	Weight	750g
	Dimension	180*115*127(MM)
Environment	Working	Temp□5 ~ 45°C□ Humidity□10 ~ 80%
	Storage	Temp□-10 ~ 50°C □Humidity□10 ~ 90%□No dew□
Reliability parameter	Print Head Life	100KM□print density≤12.5□
Software	Driver	Android,IOS,Linux,,WinXP,Win7,Win8,Win8.1,Win10

Application:

Shopping malls, restaurants, stores, warehousing, taxation, banking, medical, postal